TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 19; & 24, T20-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 201-02)

Set a post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. mkd. ¼ S on W. face; from which
An Alder 3" dia., bears S.5°E., 27 lks. dist. mkd. ¼ S BT
An Alder 3" dia., bears N.45°W., 95 lks. dist. mkd. ¼ S BT

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11675)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

¼
S 24 | S 19
1951

from which
A Cedar 36" dia., bears S.14°45'E., 63 lks. mkd. ¼ S19 BT.
A Cedar 50" dia., bears S.60½°W., 40 lks. mkd. ¼ S24 BT.
The ¼ cor. is located on a steep NE. slope, 1.90 chs. E. of a spur which slopes North.

Stephen Stys - For: Roseburg Resources Co. - 3/2024 - M184-18

Found - A 2½" brass cap on a 1" iron pipe as set per record and (properly)marked.
A 36" Cedar stump, with open face bears S.15°E., 41.5' (S.14°45'E., per record). Added a new tag.
A 50" Cedar stump, with open face bears S.60°30'W., 26.4' (per record). Added a new tag.
New BOs- A steel post bears south 1.5'.
A steel post bears west 1.5'.
New BTs- A 21" Alder, bark scribed "W ¼ S19 BT" with X-chop and tag bears S.54°E., 47.3' to a spike at side center.
A 21" Alder, bark scribed "E ¼ S24 BT" with X-chop and tag bears S.83°W., 19.6' to a spike at side center.
A 19" Cedar, faced & scribed "E ¼ S24 BT" with X-chop and tag bears N.42°W., 31.4' to a spike at side center.
LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS:
N: 43°49'10.2" W: 123°49'42.0"