

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T20-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 202)

A Fir 10" dia., which I mark T20S S18 on NE.; R9W S19 on SE.; R10W S24 on SW.; S13 on NW. sides, with 3 notches on N. and S. sides, for corner to secs. 18, 19, 13 and 24; from which

A Fir 48" dia., bears N.30°E., 30 lks. dist. mkd. T20S R9W S18 BT.

A Fir 48" dia., bears S.7½°E., 18 lks. dist. mkd. T20S R9W S19 BT.

A Fir 30" dia., bears S.60°W., 110 lks. dist. mkd. T20S R10W S24 BT.

A Fir 24" dia., bears N.75°W., 38 lks. dist. mkd. T20S R10W S13 BT.

Cor. Fd. OK in GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Pgs 221-22)

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11676)

The Sec. Cor., marked by the decayed stump of the original corner tree, 16" dia., with blaze rotted away; through the root crown of the stump.

Set an iron post 3 ft. long, 2" dia., 28" in the ground with brass cap mkd:

T 20 S	
R 10 W	R 9 W
S 13	S 18
S 24	S 19
1951	

from which the remaining original bearing trees:

A Fir 60" dia., bears S.31¼°E., 34 lks. dist., with the scribe marks T 2 R visible on old bark blaze. (Rec. desc., N.30°E., 30 lks.)

A Fir 54" dia., bears S.9°E., 20 lks. dist. mkd. T20S R9W S19 BT on old bark blaze. (Rec. S.7½°E., 18 lks.)

A Fir 48" dia., bears N.75°W., 34 lks. dist., with old bark blaze nearly scaled away. (Rec. dist., 38 lks.) I re-blaze this tree below the original blaze and mark T20S R10W S13 BT.

Place a yellow location poster on each of the original bearing trees, and mark new bearing trees as follows:

A Fir 50" dia., bears S.24°E., 32 lks. dist., mkd. T20S R9W S19 BT.

A Cedar 8" dia., bears S.31½°W., 61 lks. dist. mkd. T20S R10W S24 BT.

CONT.

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Stephen Stys - For: Roseburg Resources Co. - 3/2024 - M184-18

-
- Found - A 2½" (BLM) brass cap on a 2" iron pipe (properly)mkd. Set steel post alongside monument.
 - A 60" rotten fir stump, with no marks bears S.31°E., 22.4' (S.31°15'E., per record).
 - A 54" rotten fir stump, with no marks bears S.9°E., 13.2' (Per record).
 - A 48" rotten fir stump, with no marks bears N.75°W., 22.4' (Per record).
 - NEW BTS- A 19" Alder, bark scribed "SE S13 BT" with X-chop and tag bears N.13°W., 1.4' to a spike at side center.
 - A 40" cedar, faced & scribed "NW S19 BT" with X-chop and tag bears S.35°E., 22.4' to a spike at side center.
 - A 14" cedar, faced & scribed "NE S24 BT" with X-chop and tag bears S.5°W., 21.7' to a spike at side center.
 - A 13" fir, faced & scribed "SE S13 BT" with X-chop and tag bears N.78°W 17.5' to a spike at side center.

LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS:
N: 43°49'41.1" W: 123°49'36.4"