

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 203)

A Chittim 6" dia., which I marked T20S S7 on NE.; R9W S18 on sE.; R10W S13 on SW.; S12 on NW. sides, with 2 notches on N. and 4 notches on S. sides, for cor. to secs. 7, 18, 13 and 12; from which

An Alder 10" dia., bears N.61½°E., 37 lks. dist. mkd. T20S R9W S7 BT.

A Fir 36" dia., bears S.35°E., 37 lks. dist. mkd. T20S R9W S18 BT.

A Hemlock 5" dia., bears S.46°W., 28 lks. dist. mkd. T20S R10W S13 BT.

A Fir 40" dia., bears N.30°W., 45 lks. dist. mkd. T20S R10W S12 BT.

Fd. and used in GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 210)

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 268-69)

Intersect the sec. cor., which is a Chittim 10" dia., mkd. and witnessed as described by the surveyor general, except that the SE. and SW. bearing trees are dead. I replace these bearing trees.

From the corner

(Old bearing tree), an Alder 16" dia., bears N.61½°E., 37 lks. dist. mkd. T20S R9W S7 BT.

(New bearing tree) an Alder 12" dia., bears S.69°E., 58 lks. dist. mkd. T20S R9W S18 BT.

(New bearing tree) a Vine Maple 6" dia., bears S.10°W., 18 lks. dist. mkd. T20S R10W S13 BT.

(Old bearing tree), a Fir 45" dia., bears N.30°W., 45 lks. dist. mkd. T20S R10W S12 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11678)

The sec. cor., marked by the decayed stump of a cascara tree, 10" dia., from which

A dead Alder 16" dia., bears N.61½°E., 37 lks. dist., mkd. T20S R9W S7BT, on decayed blaze. (An 1891 BT.)

(Cont. Next Page)

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13, T20-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

An alder 16" dia., bears S.69°E., 58 lks. dist., mkd. T20S R9W S18 BT on the bark. (A 1921 bearing tree)

A dead Fir 36" dia., bears S.30°E., 37 lks. dist., mkd. T20S R9W S18 BT on bark blaze. (An 1891 BT; rec. brg. S.35°E.)

A Fir 55" dia., bears N.30°W., 45 lks. dist. mkd. T20S R10W S12 BT on bark blaze. (1921 BT)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S	
R 10 W	R 9 W
S 12	S 7
S 13	S 18
1952	

from which new bearing trees:

A Hemlock 8" dia., bears N.71°E., 71 lks. dist. mkd. T20S R9W S7 BT.

A Hemlock 12" dia., bears S.56°W., 33 lks. dist. mkd. T20S R10W S13 BT.

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23084)

The cor. of secs. 7, 12, 13, & 18, monumented with an iron post, 2" dia., firmly set, projecting 9" above ground, with brass cap (properly) mkd.

from which an original bearing tree

A fir, 62" dia., bears N.30°W., 29.7 ft., with scribe marks T20S R10W S12 BT visible on a bark blaze.

and the bearing trees mkd. by Tillman in 1951-52

A hemlock, 29" dia., bears N.71°E., 46.9 ft., with a healed blaze.

A hemlock, 32" dia., bears S.52½°W., 21.8 ft., with a healed blaze. (Record, S.56°W.)

and a new bearing tree

A hemlock, 25" dia., bears S.88°E., 43.1 ft., mkd. T20S R9W S18 BT.

Jerry Estabrook - For: Roseburg Resources Co. - 5/2021 - M179-43

Found - A 2" iron pipe with 2 1/2" brass cap marked "T20S R10W R9W S7 S12 S13 S18 1952" per BLM PLAT # 1398, DCSO records VOL. 27 PG 11678. Set steel post along side.

Continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13, T20-10

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Fd BTs- An original 63" fir with visible bark scribe and tag bears N.30°W., 29.7'.
A 30" Hemlock with healed face and tag bears N.71°E., 46.9'.
A 24" Hemlock with healed face and tag bears S.88°E., 43.1'.
A 32" Hemlock with healed face and tag bears S.52°30'W., 21.8'.
LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS (not survey grade) : N: 43°50'33.0" W: 123°49'35.9"

Jerry Estabrook - For: Roseburg Resources - 12/2021 - M180-35

Found - A 2" iron pipe with 2½" brass cap marked "T20S R10W R9W S7 S12 S13 S18 1952" per BLM plat # 1398, DCSO records Vol. 27 Pg 11678.

Set Steel post along side.

FD BTs - An original 63" fir with visible bark scribe and tag bears N.30°W., 29.7'.
A 30" Hemlock with healed face and tag bears N.71°E., 46.9'.
A 24" Hemlock with healed face and tag bears S.88°E., 43.1'.
A 32" Hemlock with healed face and tag bears S.52°30'W., 21.8'.

LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS:
N: 43'50'33.0" W: 123'49'35.9"