

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100538

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 268)

Apportioned distance.
Set an iron post 3 ft. long, 1" dia., 27" in the ground for ¼ sec. cor. of sec.12 only, with brass cap mkd. ¼ S 12 1921

from which
An Alder 18" dia., bears S.66°W., 40 lks. dist. mkd. ¼ S12 BT.
A Fir 40" dia., bears N.25°W., 13 lks. dist. mkd. ¼ S12 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11678-79)

The ¼ sec. cor. of sec. 12, monumented with an iron post 1" dia., 8" above ground, firmly set, with brass cap mkd. in 1921, from which
A Fir 54" dia., bears N.25°W., 13 lks. dist., marked ¼ S12 BT. (A Mensch bearing tree)
An Alder 20" dia., bears S.81°45'W., 80 lks. dist. mkd. ¼ S12 BT. (A new bearing tree)

Jerry Estabrook - For: Roseburg Resources Co. - 5/2021 - M179-43

Found - A 1" Iron pipe per BLM plat #1398, DCSO records Vol. 27 Pgs 11678-11679. Note record brass cap is now gone.
Set steel post along side.
FD BTs- A 54" Fir snag with healed face and tag bears N.25°W., 8.6'.
New BTs- A 20" Fir, face scribed "X BT" with X-chop and tag bears S.21°E., 11.3' to a spike at side center.
A 14" Fir, face scribed "E¼ S12 BT" with X-chop and tag bears S.64°W., 28.2' to a spike at side center.
LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS (not survey grade) N: 43°50'52.7" W: 123°49'41.7"