TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100568

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12, T20-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 267)

Apportioned distance.
Set an iron post 3 ft. long, 2" dia., 26" in the ground for cor. of secs. 1 and 12, with brass cap mkd: T20S | T20S
S1 / S12 | R9W
R10W | S7
1921

from which
A Fir 30" dia., bears S.31°W., 42 lks. dist. mkd. T20S R10W S12 BT.
A Cedar 24" dia., bears N.65°W., 11 lks. dist. mkd. T20S R10W S1 BT.

Fd. OK and used in BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11679)

Jerry Estabrook - For: Roseburg Resources - 12/2021 - M180-35

Found - 2" iron pipe per DCSO records Vol 1 PG 267.
The record brass cap is now broken off.
Fd BTs- A 51" Fir with healed face bears S.31°W., 27.7'.
Placed new tag on BT.
A 44" Cedar with rotten face bears N.65°W., 7.2'.
Placed new tag on BT.
New BT - A 10" fir, face scribed "X BT" with X-Chop and tag bears S.31°E., 12.9' TO A SPIKE AT SIDE CENTER.
New BO - A steel post bears north 1.0'.
LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS:
N: 43°51'12.1" W: 123°49'46.9"