

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 211)

Set post 4 ft. long, 4" sq., 24" in the ground for cor. of secs. 6, 7, 1 and 12, marked T20S S6 on NE.; R9W S7 on SE.; R10W S12 on SW.; S1 on NW. faces, with 5 notches on S. and 1 on N. edges; from which
Hemlock 10" dia., bears N.50°E., 63 lks. dist. mkd. T20S R9W S6 BT.
Fir 8" dia., bears S.20°E., 41 lks. dist. mkd. T20S R9W S7 BT.
Chittem 7" dia., bears S.27°W., 67 lks. dist. mkd. T20S R10W S12 BT.
Fir 9" dia., bears N.41°W., 60 lks. dist. mkd T20S R10W S1 BT.

GL0 resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 266-67)

Point of intersection with line bet. secs. 6 and 7, determined as hereinafter set forth.
Set an iron post 3 ft. long, 2" dia., 26" in the ground for closing cor. of secs. 6 & 7, with brass cap mkd.
T20S
T20S S6 CC
R10W S7
S1 R9W
1921
from which
A Cedar 30" dia., bears N.37°E., 54 lks. dist. mkd. T20S R9W S6 CC BT.
An Alder 7" dia., bears S.45°E., 9 lks. dist. mkd. T20S R9W S7 CC BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11680)

The closing cor., monumented with an iron post, 2" dia., 8" above ground, firmly set, with brass cap mkd. in 1921, from which
A Cedar 30" dia., bears N.37°E., 52 lks. dist., plainly blazed and healed. (A Mensch bearing tree; rec. dist. 54 lks.)
A Cedar 40" dia., bears S.82½°E., 93 lks. dist., mkd. T20S R9W S7 CC BT. (A new bearing tree)

(Cont. Next Page)

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - John M. Powell, and crew -
July 10, 1968 - C.S. File 53/66-68

Found - Concrete filled I.P., no brass cap, broken off.
Orig. 30" now 34" Cedar, alive, N.37°E., 34.3 ft.,
shows good scar. Rescribe "T20S R9W S6 CC CS BT"
Orig. 40" Cedar, now 42" sawed stump, S.82½°E., 61.4
ft., scribe visible.
No other trees to SE. No suitable trees close NE.
or W.

Corner pipe was under logging debris which we removed.
Set brass cap at cor. mkd: County Surveyors Office 1968

T 20 S
R9W | S 6 R10W
 | S 7

Deposit old pipe alongside.
Cor. lies approx. 600 ft. W. of ridge, course N. & S. and on
N. side of ravine 15 ft. in logged off unit.

Jerry Estabrook - For: Roseburg Resources - 12/2021 - M180-35

Found - A 2" iron pipe with brass cap marked "T20S R9W R10W
S6 S7 1968"
An original 43" cedar with healed face and tag bears
N.37°E., 34.3'.
An original 40" cedar stump with tag bears
S.82°30'E., 61.4'.

New - A 30" Maple, bark scribed "X BT with X-chop and tag
bears N.72°W., 36.1' to a spike at side center.
A steel post bears north 1.5'.
A steel post bears east 1.5'.

LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS:
N: 43°51'22.2" W:123°49'38.6"