

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 211)

-----  
Set post 4 ft. long, 3½" sq., 24" in the ground, for ¼ sec. cor. mkd. ¼ S on W. face; from which a  
Hemlock 15" dia., bears N.31°E., 76 lks. dist. mkd. ¼ S BT  
Fir 10" dia., bears S.40°W., 63 lks. dist. mkd. ¼ S BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 266)

-----  
Set an iron post 3 ft. long, 1" dia., 27" in the ground for ¼ sec. cor. of sec. 6 only, with brass cap mkd: ¼  
S6  
1921  
from which  
A Cedar 5" dia., bears N.10°E., 8 lks. dist. mkd. ¼ S6 BT.  
A Fir 24" dia., bears S.44°E., 41 lks. dist. mkd. ¼ S6 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11680-81)

-----  
The ¼ sec. cor., determined at the record bearing and distance from the remaining Mensch bearing tree, as follows:  
A Fir stub 26" dia., bears S.44°E., 41 lks. dist., with blaze healed.  
The iron post set by Mensch has been carried off in a landslide, which also uprooted the other bearing tree, a Cedar 12" dia., now found lying down the slope from its original position, with blaze healed.  
At the corner point  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd: ¼ S 6  
1952  
from which new bearing trees:  
A Fir 18" dia., bears S.43°W., 14 lks. dist., mkd. with an X at breast height and the letters BT at the base.  
A Cascara 8" dia., bears N.14½°W., 26 lks. dist., mkd. with an X at breast height and the letters BT at the base.  
There are no suitable trees available E. of line due to the land slide.