

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 122700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 31 only, T19-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 44 Page(s) 17052-53)

In ravine, course SE., Set a Fir post 3 ft. long, 4" sq., 24" in the ground for $\frac{1}{4}$ sec.cor. mkd. $\frac{1}{4}$ S31 on N. face, from which

An Alder 7" dia., bears N.19°E., 12 lks. dist., mkd. $\frac{1}{4}$ S BT.

An Alder 7" dia., bears N.11°W., 13 lks. dist., mkd. $\frac{1}{4}$ S BT.

The old $\frac{1}{4}$ sec. cor. bears E. 5 lks. dist. I destroy it.
* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 372)

(Apportioned distance) Set an iron post 3 ft. long, 1" dia., 27" in the ground, for $\frac{1}{4}$ sec.cor. of sec. 31 only, with brass cap marked: $\frac{1}{4}$ S 31

1921

from which

An Alder 28" dia., bears N.19°E., 30 lks. dist. mkd. $\frac{1}{4}$ S31 BT.

A Fir 14" dia., bears N.83°W., 28 lks. dist. mkd. $\frac{1}{4}$ S31 BT