

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 137500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 7 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 392)

Point at 40.00 chs. westing from cor. of secs. 7 & 8.
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for
¼ sec. cor. of sec. 7 only, with brass cap marked
¼ S7
1921

from which
A fir, 18" dia., bears N.14°E., 16 lks., mkd: ¼ S7 BT.
A fir, 24" dia., bears N.55°W., 29 lks., mkd: ¼ S7 BT.
(The ¼ cor. to sec. 18 (North) bears S.89°04'E., 2.50 chains)

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12531-2)

The ¼ sec. cor. of sec. 7 only, monumented by Mensch in 1921, with an iron post, 1" dia., 9" above ground, firmly set, but badly rusted, with brass cap (properly) marked.
At the corner point, in place of rusted iron post,
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked: ¼ S 7
1954

from which
A fir snag, 16" dia., bears N.14°E., 16 lks., mkd: ¼ S7 BT on unhealed blaze. (Old BT)
A yew, 20" dia., bears N.24°45'E., 68 lks., mkd: ¼ S7 BT. (New BT)
A cedar, 20" dia., bears N.62°W., 54 lks., mkd: ¼ S7 BT. (New BT)
A fir snag, 30" dia., bears N.55°W., 31 lks., plainly blazed & healed. (Old BT; rec. 29 lks.)
Deposit the old iron post at base of the new one.
(The ¼ cor. to sec. 18 (North) bears S.88°09'E., 2.48 chains)