

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 329)

Set a sandstone, 11x9x6", 8" in the ground, for ¼ sec. cor., marked ¼ S on N face; and raised a mound of stone, 1½ ft. high and 2 ft. base, alongside. Pits Impracticable.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12522)

Point for the ¼ sec. cor. of secs. 19 & 30, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼ S 19
S 30
1953

from which
A fir, 28" dia., bears N.43°W., 46 lks., mkd: ¼ S19 BT.
A fir, 30" dia., bears S.61°E., 23 lks., mkd: ¼ S30 BT.

BLM dependent resurvey by Harvey E. Wofford, Cadastral Surveyor under Group #1090, surveyed April/May 1982 - (DCSO records Vol. 45 Page(s) 17461)

The ¼ sec. cor. of secs. 19 & 30, monumented with an iron post, 1" dia., firmly set, projecting 4" above ground with brass cap (properly) mkd.,

from which BTs mkd. by Tillman & Gawron
A roothole, bears S.61°E., 23 lks. with a down fir alongside, 32" dia., with a healed blaze.
A fir, 33" dia., bears N.43°W., 50 lks., with a healed blaze. (Rec. 46 lks.)
and a new BT
A cedar, 15" dia., bears S.66½°W., 79 lks., mkd: ¼ S30 BT.