

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 44 Page(s) 17053)

Summit of ridge, bears NE. & SW. Set a basalt stone 16x8x8 ins., 12" in the ground for cor. of secs. 31 & 32, marked with 5 notches on E. and 1 notch on W. edges, and raised a mound of stone, 2 ft. base, 1½ ft. high W. of cor. No trees within limits.

The old cor. bears East 7 lks. dist. I destroy it.
* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 373)

(Apportioned distance) Set an iron post 3 ft. long, 2" dia., 27" in the ground for cor. of secs. 31 & 32, T19S R9W., with brass cap mkd:
T19S R9W
S31 S32
T20S R9W
S6
1921

from which
A Fir 12" dia., bears N.26°E., 30 lks. dist., mkd. T19S R9W S32 BT.
A Maple 18" dia., bears N.24°W., 41 lks. dist. mkd. T19S R9W S31 BT.

Survey by Robert Ward, Jr., LS #1091 - For: Siuslaw National Forest - June 1991 - M 113-37 A & B

Found - 1921 GLO brass cap attached to a badly rusted iron pipe.
17" Fir bears N.21°E., 20.4 ft., healed face.
Set USFS alum. corner monument stamped "T19S R9W S31 S32 T20S R9W S6 LS 1091 1991."
New BTs- 23" Fir bears S.34°E., 29.1 ft., scribed T20S R9W S6 BT.
15" Maple bears S.16°W., 7.9 ft. bark scribed T20S R9W S6 BT.
25" Maple bears N.73°W., 26.1 ft. bark scribed T19S R9W S31 BT.