

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 178500

PRIMARY CORNER DESCRIPTION South Cor. Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 391)

-----  
Point at 80.00 chs. westing from cor. of secs. 8 & 9.  
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 7 & 8 with brass cap marked:

T20S|R9W  
S 7|S 8  
S 18  
1921

from which

A maple, 18" dia., bears N.61°E., 23 lks., mkd: T20S R9W S8 BT.

A vine maple, 8" dia., bears N.32°W., 23 lks., mkd: T20S R9W S7 BT.

-----  
(The N cor. of Secs. 17 & 18 bears S.89°08'E., 2.39 chains)

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12530)

-----  
The cor. of secs. 7 & 8, on the N bdy. of sec. 18 monumented by Mensch, in 1921, with an iron post, 2" dia., 8" above ground, firmly set, marked & witnessed as described in the official record.