

PRIMARY CORNER DESCRIPTION Sec Cor for 31 & 32; 5 & 6, T21-9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Wm. Thiel under Contract #260 dated April 17, 1877 - (DCSO records Vol. 1 Page(s) 303-04)

Set a Chitten post for corner to secs. 31, 32, 6 and 5; from which

- A Fir 60" dia., bears S.27°W., 80 lks. dist.
- A Fir 50" dia., bears S.71¼°E., 41 lks. dist.
- A Maple 36" dia., bears N.66½°W., 1.01 chs. dist.
- An Alder 18" dia., bears N.18 3/4°E., 1.20 chs. dist.

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 1 Page(s) 365)

The cor. to secs. 31 & 32. Old post greatly decayed, which I destroyed and set Alder post, ft. long, 4" sq., 24" in the ground on side hill, sloping E., mkd. T20S S32 on the NE. and R9W S31 on the NW., with 5 notches on the E. and 1 notch on the W. edges; from which

- A Fir stump, 50" dia., bears S.71°15'E., 38 lks. dist. mkd. T21S R9W S5 BT.
- A Fir 60" dia., bears S.27°W., 88 lks. dist., mkd. T21S R9W S6 BT.
- A Maple 36" dia., bears N.66°30'W., 107 lks. dist. mkd. T20S R9W S31 BT.

The bearing tree in sec. 32 had been destroyed; I marked
An Alder 6" dia., bears N.16°45'E., 182 lks. dist. mkd. T20S R9W S32 BT.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12447)

The cor. of secs. 5, 6, 31 & 32, perpetuated with an iron pipe, 2" dia., 8" above ground, firmly set, with unmarked pipe cap, from which the remaining original bearing trees:

- A sawed Fir stump 50" dia., bears S.71¼°E., 41 lks. dist., with scribe marks weathered away from unhealed blaze. (Thiel record, 41 lks. dist., Gesner, 38 lks. dist.)
- A sawed Fir stump, 60" dia., bears S.27°W., 83 lks. dist., with scribe marks weathered away from unhealed blaze. (Thiel record, 80 lks. dist., Gesner, 88 lks. dist.)
- A Maple 36" dia., bears N.66½°W., 107 lks. dist., with blaze healed. (Thiel record, 101 lks., Gesner, 107 lks. dist.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground,
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 31 & 32; 5 & 6, T21-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

with brass cap mkd: T 20 S R 9 W
 S 31 | S 32
 S 6 | S 5
 T 21 S
 1953

from which new bearing trees,
A Maple 11" dia., bears N.2¼°E., 156 lks. dist. mkd. T20S R9W S32 BT.
A Fir 33" dia., bears S.82°45'E., 117 lks. dist. mkd. T21S R9W S5 BT. (This tree is the anchor for a flood gate in fence across Buck Creek.)
A Cedar 34" dia., bears S.85½°W., 88 lks. dist., mkd. T21S R9W S6 BT.
Reset the iron pipe alongside the iron post.
Cor. is located in a fence row which extends N.88°45'E. and S.89°23'W.

Douglas Co. Surveyors Office - John M. Powell, and crew -
Sept. 1969 - C.S. File 53/66-16

Found - Unmarked pipe cap & also GLO brass cap mkd. in 1953.
34" Cedar now stob, S.85½°W., 58.1 ft., scribe visible.
33" D.Fir now stump, S.83°E., 77.2 ft.
11" now 13" Maple N.2°E., 103.0 ft., partial scribe visible, mostly grown over.
New BTs- 14" Maple N.7°E., 22.3 ft. mkd. T20S R9W S32 CS BT.
12" Maple N.46°W., 22.6 ft. mkd. T20S R9W S31 CS BT.
15" D.Fir S.23°E., 23.8 ft. mkd. T21S R9W S5 CS BT.
16" Maple S.50°W., 21.7 ft. mkd. T21S R9W S6 CS BT.
Corner is in E-W fence line.

Fd. OK, Feb. 1992 by R. Ward - M 114-48

Survey by Robert Ward, Jr. - For: International Paper Co. -
Feb. 1993 - M 116-61

Found - 2½" BLM brass cap with the following accessories:
17" Maple, N.8°E., 22.1 ft.
11" Maple, N.42°W., 22.4 ft.
17" Maple, S.47°W., 21.1 ft.
Fir BT is uprooted.
New BT - 20" Alder S.30°E., 30.8 ft., bark scribed "T21S R9W S5 BT"