TOWNSHIP 20 RANGE 9 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

---

GLO survey by William Thiel under contract 260 dated Apr. 17, 1877 - (DCSO records Vol. 1 Page(s) 311)

---

Set ¼ sec. post; from which
A fir, 54" dia., bears N.89¾°E., 88 lks.
A fir, 48" dia., bears S.66°W., 1.17 chs.

---

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12516

---

Point for the ¼ sec. cor. of secs. 31 & 32, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked: ¼
S 31|S 32
1953
from which
A fir, 22" dia., bears N.34°E., 9 lks., mkd: ¼ S32 BT.
A fir, 29" dia., bears N.58½°W., 23 lks., mkd: ¼ S31 BT.

---

Fd. & used on BLM dependent resurvey by Owen C. Chatters II, Cadastral Surveyor, under Group #777, surveyed May/June 1972 - (DCSO rec. Vol. 36 Page(s) 15009-10)- Fd brass cap & 2 BTs)

---

Fd. Ok by Eimstad, Aug. 1981, M89-13
Fd. Ok by Rob Ward, 2/1992, M114-48

---

Rob Ward - For: International Paper Co. - 2/1993 - M116-61

---

Found - 2½" BLM brass cap with the following accessories,
33" Fir N.58°W., 14.8'
21" Fir stump, N.29°E., 5.7'
New BT - 30" Fir N.5°E., 35'. Blazed & scribed "¼ S32 BT"

---