

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Thiel under contract 260 dated Apr. 17, 1877 - (DCSO records Vol. 1 Page(s) 311)

-----  
Set post to corner of sections 29, 30, 31, & 32; from which  
A maple, 16" dia., bears N.21¼°W., 17 lks.  
A fir, 28" dia., bears S.36°W., 0.15 chs.  
A fir, 18" dia., bears S.63½°E., 58 lks.  
A fir, 26" dia., bears N.22½°E., 33 lks.

BLM dependent resurvey by Thomas A Tillman & Joseph S Gawron, under Group #306, surveyed May 1953 - Oct. 1954 (DCSO recs. Vol. 29 Page(s) 12516-7)

-----  
The cor. of secs. 29, 30, 31, & 32, determined from the orig. BTs as follows:

- A sawed fir stump, 44" dia., bears N.22½°E., 34½ lks., mkd. R9W on exposed portion of blaze. (Rec. 33 lks.)
- A sawed fir stump, 40" dia., bears S.63½°E., 60 lks., plainly blazed & healed. (Rec. 58 lks.)
- A sawed fir stump, 50" dia., bears S.36°W., 16 lks., mkd. BT in negative on overgrowth. (Rec. 15 lks.)

At the corner point

Set an iron post, 3' long, 2" dia., 28" in the ground, with brass cap marked:

T20S R9W  
S 30 | S 29  
-----  
S 31 | S 32  
1953

from which new BTs,

- A fir, 16" dia., bears N.23°45'E., 56 lks., mkd: T20S R9W S29 BT.
- A fir, 18" dia. bears S.78°E. 65 lks. mkd: T20S R9W S32 BT
- A fir, 22" dia., bears S.59½°W., 63 lks., mkd: T20S R9W S31 BT.
- A fir, 18" dia., bears N.42¼°W., 54 lks., mkd: T20S R9W S30 BT.

BLM dependent resurvey by Owen C. Chatters II, Cadastral Surveyor, under Group #777, surveyed May/June 1972 - (DCSO rec. Vol. 36 Page(s) 15010-11)

-----  
The cor. of secs. 29, 30, 31, & 32, monumented with an iron post, 2" dia., firmly set, protruding 10" above ground, with brass cap (properly) mkd., from which the remains of the Orig. BTs.

- A sawed fir stump, 50" dia., bears N.22½°E., 34½ lks., mkd. R9W visible on open blaze.

continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stump, 54" dia., bears S.63½°E., 60 lks., mkd: with healed blaze.  
A sawed fir stump, 50" dia., bears S.36°W., 16 lks., with reverse scribe marks BT visible on over growth.  
and BTs mkd. by Tillman & Gawron  
A fir, 28" dia., bears N.23¾°E., 56 lks., with healed blaze.  
A hemlock, 30" dia., bears S.78°E., 65 lks., with healed blaze.  
A sawed fir stump, 26" dia., bears S.59½°W., 63 lks., with healed blaze.  
A sawed fir stump, 24" dia., bears N.42¼°W., 54 lks., with healed blaze.  
and new BTs  
A cedar, 15" dia., bears S.62°W., 57½ lks., mkd: T20S R9W S31 BT.  
A fir, 13" dia., bears N.38½°W., 57 lks., mkd: T20S R9W S30 BT.

Fd. Ok 8/1981 - W. Eimstad - M89-13