

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 331)

Set a sandstone, 24x18x6", 18" in the ground for cor. to secs. 17, 18, 19, & 20, marked with 3 notches on S and 5 notches on E edges; from which

A fir, 24" dia., bears N.62½°E., 14 lks., mkd: T20S R9W S17 BT.

A fir, 30" dia. bears S.58°E. 38 lks. mkd: T20S R9W S20 BT

A fir, 40" dia. bears S.62°W. 16 lks. mkd: T20S R9W S19 BT

A fir, 32" dia. bears N.89°W. 40 lks. mkd: T20S R9W S18 BT

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12524)

The cor. of secs. 17, 18, 19, & 20, monumented with a sandstone, 24x18x6", marked with a cross (X) on top, the other marks weathered away, firmly set 12" in the ground, from which the orig. BTs:

A fir, 36" dia., bears N.62½°E., 18 lks., mkd: T20S R9W S17 BT on bark blaze. (Rec. dist. 14 lks.)

A fir, 48" dia., bears S.62°E., 38 lks., mkd: T20S R9W S20 BT on bark blaze. (Rec. bearing S.58°E.)

A fir, 50" dia., bears S.62°W., 17 lks., mkd. with illegible scribe marks on bark blaze. (Rec. dist. 16 lks.)

An uprooted fir, 36" dia., with no marks remaining, the stump hole of which bears N.89°W., 4 lks. (Rec. dist. 40 lks.)

An iron pipe, 4 ft. long, 2" dia., is found lying beside the marked stone, with iron pipe marked

| | |
|--------|-------|
| 18 | 17 |
| T 20 S | R 9 W |
| 19 | 20 |

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

| | |
|------|------|
| T20S | R9W |
| S 18 | S 17 |
| S 19 | S 20 |
| 1953 | |

from which a new BT

A fir, 45" dia., bears N.17°W., 105 lks., mkd: T20S R9W S18 BT.

Reset the sandstone and the iron pipe alongside the iron post.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

| Alias | Description |
|-------|-------------|
| | |
| | |
| | |
| | |

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23110-1)

The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2" dia., firmly set, projecting 16" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A fir stump, 32" dia, bears N.62½°E., 11.9 ft., no marks visible.

A fir stump, 35" dia, bears S.62°E., 25.1 ft., no marks visible.

A fir stump, 42" dia., bears S.62°W., 9.6 ft., no marks visible. (Record, 11.2 ft.)

and the remains of a bearing tree mkd. by Tillman and Gawron in 1953-54

A fir stump, 50" dia, bears N.17°W., 69.3 ft., with scribe marks 20S R9W S18 BT visible on partially healed blaze. and new bearing trees

A fir, 12" dia, bears N.42°E., 21.4 ft., mkd. T20S R9W S17 BT.

A fir, 12" dia., bears S.46½°E., 11.7 ft., mkd. T20S R9W S20 BT.

A fir, 10" dia, bears S.37°W., 4.7 ft., mkd. T20S R9W S19 BT.

A fir, 13" dia., bears N.11½°W., 11.9 ft., mkd. T20S R9W S18 BT.

Add a collar of stone around the cor.

An iron post, 2" dia., loosely set and leaning, projecting 24" above ground, with galvanized cap mkd. 18 17 T20S R9W 19 20, recovered lying loose by Tillman and Gawron in 1953-54 and reset alongside the cor., was found alongside.