

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 333)

Set a post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which
An Alder, 4" dia., bears N.84°E., 23 lks., mkd: ¼ S BT.
A hazel, 3" dia., bears S.27°W., 41 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12527)

Point for the ¼ sec. cor. of secs. 17 & 18, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 18|S 17
1953

from which

A fir, 36" dia., bears N.34°E., 19 lks., mkd: ¼ S17 BT.
A fir, 36" dia., bears S.48°W., 27 lks., mkd: ¼ S18 BT.