

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6 (Witness Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 402)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor. with brass cap marked:

1/4
S 6 | S 5
1921

from which

- A fir, 30" dia., bears N.22°E., 31 lks., mkd: 1/4 S5 BT.
- A fir, 12" dia., bears N.48°W., 11 lks., mkd: 1/4 S6 BT.

Douglas Co. Surveyors Office - Milo Godfrey, Deputy - Wm. Stoffel & Mike Stone - Sept. 1964 - C.S. File 53/66-47

Corner renewed from trees referenced out from 1/4 corner by Merle Weaver (See affidavit in C.S. File 53/66-47) to wit:

- 8" Maple N.85°W., 27.0 ft.
- 14" Fir to the S.W. 47.8 ft.

Alum. tags on both of these trees gave distance to 1/4 cor. The corner position as measured from these trees, falls part way up the cut bank on the west side of Forest Service Rd.

Set - Wit. cor. 80 ft. S of 1/4 cor. mkd: County Surveyors Office T20S R9W WC 1/4 S6/S5 80 ft. N to cor.

- New BTs- 14" D.Fir, N.20°W., 40.4 ft. mkd: WC 1/4 S6 CS BT
- 16" D.Fir, South 45.2 ft. mkd: WC 1/4 S6 CS BT

Note - Corner is approximately 30 ft. West of Forest Service Road.