

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 228700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 32 only, T19-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 44 Page(s) 17053)

-----  
Set a Fir post 3 ft. long, 4" sq., 24" in the ground for the ¼ sec. cor. mkd. ¼ S32 on N. face from which  
A Fir 4" dia., bears N.80°E., 10 lks. dist. mkd. ¼ SBT.  
A Hemlock 4" dia., bears N.2°W., 25 lks. dist. mkd. ¼ S BT  
The old ¼ sec. cor. bears E. 8 lks. dist. I destroy it.  
\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 374)

-----  
(Apportioned distance) Set an iron post 3 ft. long, 1" dia., 27" in the ground for re-established ¼ sec. cor. of sec. 32 only, with brass cap mkd. ¼ S 32  
1921  
from which  
A Fir 36" dia., bears N.38°E., 88 lks. dist., mkd. ¼ S32 BT.  
An Alder 24" dia., bears N.27°W., 33 lks. dist. mkd. ¼ S32 BT.