

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 238500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 8 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 390)

Point at 40.00 chs. westing from cor. of secs. 8 & 9.
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for
¼ sec. cor. of sec. 8 only, with brass cap marked:
¼ S8
1921

from which
A fir, 60" dia., bears N.30°E., 35 lks., mkd: ¼ S8 BT.
A chittem, 8" dia., bears N.63°W., 34 lks., mkd: ¼ S8 BT.
(The North ¼ cor. sec. 17 only bears S.89°32'E., 1.79 chains)

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12530)

The ¼ sec. cor. of sec. 8 only, monumented by Mensch in 1921, with an iron post, 1" dia., 9" above ground, firmly set, but badly rusted, with brass cap (properly) marked
At the corner point, in place of the rusted iron post.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked: ¼ S 8
1954

from which
A fir, 50" dia., bears N.32½°E., 33 lks., plainly blazed & healed. (Old BT; record, bears N.30°E., 35 lks.)
A fir, 50" dia., bears N.63¼°W., 140 lks., mkd: ¼ S8 BT. (New BT)
A cascara, 10" dia., bears N.63°W., 34 lks., with no marks remaining (Old BT)
Deposit the old iron post at the base of the new one.
(The North ¼ cor. sec. 17 only bears S.89°28'E., 1.81 chains)