

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel under contract 260 dated Apr. 17, 1877 - (DCSO records Vol. 1 Page(s) 312)

Set ¼ sec. post; from which
A maple, 15" dia., bears S.89°W., 69 lks.
A fir, 24" dia., bears N.23°W., 60 lks.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12517-8)

The ¼ sec. cor. of secs. 29 & 32, at record bearing & distance from each of the orig. BTs, as follows:
A fir, 40" dia., bears N.23°E., 60 lks., plainly blazed & healed.
A maple, 24" dia., bears S.89°W., 69 lks., plainly blazed & healed.

At the corner point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked: ¼ $\frac{S\ 29}{S\ 32}$

from which new BTs
A Maple, 8" dia., bears N.31½°W., 47 lks., mkd: ¼ S29 BT.
An Alder, 14" dia., bears S.32°E., 51 lks., mkd: ¼ S32 BT.

Fd. & used on BLM dependent resurvey by Owen C. Chatters II, Cadastral Surveyor, under Group #777, surveyed May/June 1972 - (DCSO rec. Vol. 36 Page(s) 15012)

Fd. Ok by Eimstad Aug. 1981 - M 89-13