TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 330)

Set a post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which
A fir, 4" dia., bears N.25°W., 37 lks., mkd: ¼ S BT.
A vine maple, 3" dia., bears S.3°E., 19 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12521

Point for the ¼ sec. cor. of secs. 20 & 29, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼ S 20 / S 29 / 1953

from which
A fir, 20" dia., bears N.4°E., 44 lks., mkd: ¼ S20 BT.
A fir, 20" dia., bears S.33°W., 47 lks., mkd: ¼ S29 BT.
The ¼ sec. cor. is located 34 lks. S. of top of spur, slopes E.

Fd. Ok by Les Roberts, Dec. 3, 1982 - M90-33

Les Roberts, PLS 1039 - For: International Paper Co. - Dec. 3, 1982 - M 90-33

Found - 1953 GLO BC
BTs - 24" downed fir bears N.2°E., 32.0 ft. (scar visible) 1953 BT.
New BTs- 15" fir bears S.38°E., 32.7 ft. (scribed)
17" maple bears N.39°E., 38.5 ft. (scribed)