

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 335-6)

A barberry, 5" dia., which I marked ¼ S on N face; from which
A barberry, 6" dia., bears S.68°E., 21 lks., mkd: ¼ S BT.
A fir, 15" dia., bears N.88°W., 90 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12525)

Point for the ¼ sec. cor. of secs. 17 & 20, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼ $\frac{S\ 17}{S\ 20}$
1953

from which
A fir, 54" dia., bears N.51°E., 28 lks., mkd: ¼ S17 BT.
A fir, 60" dia., bears S.76°W., 42 lks., mkd: ¼ S20 BT.

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - C.S. 56/49-3 - March 15, 1974

Found - US GL0 brass cap, 1953, properly marked with a steel fence post alongside.
BTs- 60" now 54" D.Fir stump bears S.76°W., 27.7 ft. scribing partially visible at edge of lower blaze. NOTE (This stump has had the bark removed, been treated with a liquid preservative & covered with sheet metal)
The NE BT, marked in 1953, has fallen & slid downhill out of position. The main portion of the tree has been removed in recent logging. Scribing is partially visible near base of root wad.
New B0 - A boat spike driven in the top of a 58" D.Fir stump, bears N.64°W., 33.1 ft.
Note - This corner lies on steep slope near the bottom of and approx. 150' north of a ravine in a recently logged area.