

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 17 only (North)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 337)

Set a post, 4 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S on N face; from which
A fir, 36" dia., bears S.10°E., 19 lks., mkd: 1/4 S BT.
A fir, 48" dia., bears N.88°W., 21 lks., mkd: 1/4 S BT.
This corner stands near the top of ascent on S slope.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 389-90)

Intersect true point for old 1/4 sec. cor. determined by reference to the orig. BTs, which are as described by the surveyor general, no trace of old post found. Hereafter, this cor. will refer to sec. 17 only, I obliterate marks on former BT referring to sec. 8 and at exact corner point.
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor. of sec. 17 only, with brass cap marked:

1/4 S 17
1921

from which
(Old BT) A fir, 40" dia., bears S.10°E., 19 lks., mkd: 1/4 S17 BT.
(New BT) A fir, 40" dia., bears S.20°W., 72 lks., mkd: 1/4 S17 BT.
(The South 1/4 cor. sec. 8 only bears N.89°32'W., 1.79 chains)

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12529)

The 1/4 sec. cor. of sec. 17 only, remonumented by Mensch, in 1921, with an iron post, 1" dia., 9" above ground, firmly set but rusted through to the concrete core, with brass cap (properly) marked.
At the corner point, in place of the rusted iron post,
Set an iron post, 3 ft long, 1" dia., 28" in the ground, with brass cap marked:

1/4 S 17
1954

from which
A fir, 50" dia., bears S.28°E., 52 lks., mkd: 1/4 S17 BT.
(New BT)
A fir snag, 26" dia., bears S.10°E., 25 lks., mkd: 1/4 S BT
on bark blaze. (A Thiel BT) continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 17 only (North)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir, 50" dia., bears S.21½°W., 74 lks., plainly blazed & healed. (A Mensch BT; rec. bears S.20°W., 72 lks.)
Deposit the old iron post at the base of the new one.
(The South ¼ cor. sec. 8 only bears N.89°28'W., 1.81 chains)