

PRIMARY CORNER DESCRIPTION Cor. Secs. 8 & 9 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 389)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 8 & 9, with brass cap marked:

T20S R9W
S8 | S9
S17
T20S R9W
1921

from which

A fir, 6" dia., bears N.60°E., 16 lks. mkd: T20S R9W S9 BT
A fir, 36" dia. bears N.25°W., 36 lks. mkd: T20S R9W S8 BT

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12528)

The cor. of secs. 8 & 9 on the N. bdy. of sec. 17, monumented by Mensch, in 1921, with an iron post, 2" dia., 8" above ground, firmly set, but rusted through to the concrete core, with brass cap marked

T 20 S | R 9 W
S 8 | S 9
S 17
T 20 S | R 9 W
1921

At the corner point, in place of the rusted iron post, Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T 20 S | R 9 W
S 8 | S 9
S 17
1954

from which the orig. BTs

A fir, 18" dia., bears N.60°E., 16 lks., plainly blazed & healed.
A fir, 48" dia., bears N.25°W., 36 lks., marked T20S R9W S8 BT on bark blaze.

Deposit the old iron post at base of the new one.

Stephen Swinehart, L.S. 2013 - For: USFS, Siuslaw National Forest - July 1983 - M94-77

Found - 1954 GLO brass cap (1953-54 cadastral survey)
18" fir windfall, rotten hull w/scribing bears N.63°E., 12.1 to blaze. (6" N.60°E., 10.6 ft.) root hole matches orig. calls)
continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 278500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8 & 9 only (South)

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

36" fir windfall w/healed blaze bears N.6°E., 18.0 ft. to blaze. (36" N.25°W., 23.8 ft.)
18" maple w/BT tag bears S.44¼°E., 13.1 ft. tag, S.59°E., 14.9 ft.
New BTs- 43" fir, "T20S R9W S8 BT" N.25¾°W., 51.3 ft.
34" fir, "T20S R9W S9 BT" N.70½°E., 42.6 ft.
We raised a stone mound around the monument.

Fd. BC - 10/2019 - T. Hostetter - C.S. 65/103-13