

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 335)

Set a sandstone, 24x18x5" 18" in the ground for cor. to secs. 20, 21, 16, & 17, marked with 3 notches on S & 4 notches on E edges; from which

- A fir, 36" dia. bears N.28°E. 54 lks. mkd: T20S R9W S16 BT
- A fir, 32" dia. bears S.76°E. 25 lks. mkd: T20S R9W S21 BT
- A fir, 36" dia. bears S.9°W., 13 lks. mkd: T20S R9W S20 BT
- A fir, 30" dia. bears N.27°W. 150 lks. mkd: T20S R9W S17BT

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12512-3)

The cor. of secs. 16, 17, 20, & 21, monumented with a sandstone, 24x18x5", loosely set 10" in the ground, marked with 1 groove on S face; alongside of which has been driven an iron pipe, 4 ft. long, 2" dia., 12" in the ground, with iron pipe cap marked

17 16
T 20 S R 9 W
20 21

from the sandstone, the orig. BTs,
A fir, 44" dia., bears N.28°E., 61 lks., mkd: T20S R9W S16 BT on bark blaze. (Rec. dist. 54 lks.)
A dead fir, 32" dia., bears S.76°E., 28 lks., mkd: T20S R9W S21 BT on bark blaze. (Rec. dist. 25 lks.)
A dead fir, 50" dia., bears S.9°W., 14 lks., plainly blazed & healed. (Rec. dist., 13 lks)
The orig. NW BT has been uprooted, & occupies the approx. rec. position, with traces of scribe marks visible on badly scaled bark blaze.

At the corner point
Set an iron post, 3 ft long, 2" dia., 28" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked:

T20S R9W
S 17 | S16
S 20 | S 21
1953

from which new BTs,
A fir, 30" dia., bears S.52°45'E., 106 lks., mkd: T20S R9W S21 BT.
A fir, 25" dia., bears S.70°W., 140 lks., mkd: T20S R9W S20 BT.
A fir, 36" dia. bears N.21°W. 91 lks. mkd: T20S R9W S17 BT

continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Fd. Ok by Les Roberts, Dec. 19, 1982 - M90-31

Stephen Swinehart, L.S. 2013 - For: International Paper Co. -
Nov. 1983 - M95-53

Found - 1953 GLO brass cap on 2" galv. pipe.
48" fir stump with no marks N.27 $\frac{3}{4}$ °E., 38.2. (1891
rec. N.28°E., 35.6 ft.)
26" fir stump with no marks S.78 $\frac{1}{4}$ °E., 18.1 (1891
rec. S.76°E., 16.5 ft.)
36" fir stump with no marks S.5 $\frac{3}{4}$ °W., 9.5 ft. (1891
S.9°W., 8.6 ft.)
40" fir stump, S.53 $\frac{1}{4}$ °E., 69.7 ft. (1953, S.52 $\frac{3}{4}$ °E.,
70.0 ft)
23" fir stump with healed face, S.70°W., 91.3 ft.
(1953 S.70°W., 92.4 ft.)
36" fir stump with healed face, N.19 $\frac{1}{4}$ °W., 58.8 ft.
(1953 rec. N.21°W., 60.1 ft.)

Set - We set 2 ref. monuments:
RM 1, bears N.9°52'E., 34.66 ft.
RM 2, bears S.86°26'W., 69.95 ft.
We set a steel fence post near the brass cap.
The ref. monuments set at the SW section cor are 5/8" x 30"
rebar with yellow plastic cap marked "S Swinehart" LS 2013

Fd. BC & BTs as per 1983 ren. Plus unrecorded BT: 8" fir,
scribing visible, BT Tag, bears N.61°W., 6.7 ft. - by T
Hostetter - 10/2019 - C.S. File 65/103-13

2