

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, & 17 only (north)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 336-7)

A barberry 5" in dia., which I marked for cor. to secs. 16, 17, 8, & 9, marked T20S S9 on NE, R9W S16 on SE, S17 on SW, S8 on NW face, with 4 notches on S & E edges; from which
A fir, 48" dia. bears N.89°E. 190 lks. mkd: T20S R9W S9 BT
A barberry, 8" dia., bears S.45°E., 4 lks., mkd: T20S R9W S16 BT.
A fir, 24" dia., bears S.36°W., 267 lks., mkd: T20S R9W S17 BT.
A fir, 36" dia. bears N.88°W. 155 lks. mkd: T20S R9W S8 BT

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 388)

Intersect the old cor. of secs. 8, 9, 16 & 17, which is a barberry, 8" dia., marked & witnessed as described by the surveyor general, except that the SW BT is dead. Hereafter this cor. will refer to secs. 16 & 17 only. I obliterate marks on former BT referring to secs. 8 & 9; also change marks on corner tree to refer only to secs. 16 & 17. The corner tree is now marked R9W S16 on SE & T20S S17 on SW side; from which
(Old BT) A barberry, 10" dia., bears S.45°E., 4 lks., mkd: T20S R9W S16 BT.
(New BT) A barberry, 8" dia., bears S.6°W., 39 lks., mkd: T20S R9W S17 BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12515)

The cor. of secs. 16 & 17, on the S bdy. of sec. 9, marked by a cascara, 8" dia., uprooted & lying beside corner point, with no marks remaining, from which
An uprooted fir, 44" dia., is fd. lying 6 lks., S of cor. point, point of origin not located, marked T20S r9W on bark blaze, evidently the SW BT marked by Thiel in 1891, reported dead by Mensch in 1921.
A cascara, 10" dia., bears S.6°W., 39 lks., with partial scribe marks vis. on nearly healed blaze. (A Mensch BT)
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked: continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, & 17 only (north)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

S 9
S 17|S 16
T20S R9W
1953

from which

A fir, 55" dia., bears S.48°E., 143 lks., mkd: T20S R9W
S16 BT.

A fir, 10" dia., bears S.63½°W., 79 lks., mkd: T20S R9W
S17 BT.

Stephen Swinehart, L.S. 2013 - For: USFS, Siuslaw National
Forest - July 1983 - M94-77

Found - 1953 GLO brass cap
60" fir stump, S.48°E., 94.4 ft. with visible
scribing (55", S.48°E., 94.4 ft.)

New BTs- 22" fir "T20S R9W S17 BT" bears S.37°W., 62.0 ft.
50" fir "X BT" bears N.10¾°W., 40.0 ft.

We raised a stone mound around the monument.

Fd. BC - 10/2019 - T. Hostetter - C.S. 65/103-13