

PRIMARY CORNER DESCRIPTION Cor Secs. 4, 5, 8, & 9

Alias	Description

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 396-7)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 4, 5, 8, & 9, with brass cap marked:

T20S R9W
S 5 | S 4
S 8 | S 9
1921

from which

- An Alder, 12" dia., bears N.89°E., 26 lks., mkd: T20S R9W S4 BT.
- An Alder, 6" dia., bears S.54½°E., 36 lks., mkd: T20S R9W S9 BT.
- An Alder, 8" dia., bears S.58°W., 11 lks., mkd: T20S R9W S8 BT.
- A fir, 40" dia., bears N.30°W., 35 lks mkd: T20S R9W S5 BT

BLM Dependent Resurvey by Jason A Lightbown, Cadastral Surveyor, Under Group No. 2841, Surveyed June/Oct. 2016 - (DCSO records Vol. 59 Page(s) 23608)

The cor. of secs. 3, 4, 9, & 10, perpetuated by Godfrey, based on an affidavit by Fred Zeigler, in 1964, who provided testimonial evidence of the original cor. position which had been obliterated by the creek; monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, in a collar of stone, with a brass cap (properly) mkd.

from which the remains of the bearing trees mkd. by Godfrey

- A fir stump, 52" dia., bears N.30°E., 150.3 ft., no marks visible.
- A metal-capped fir stump, 53" dia., bears N.70½°W., 62.7 ft., with scribe marks R9W S4 CS B visible on partially healed blaze.

and new bearing trees

- An alder, 12" dia., bears N.57°E., 26.4 ft., mkd. T20S R9W S3 BT on bark.
- An alder, 13" dia., bears S.44¼°E., 29.2 ft., mkd. T20S R9W S10 BT on bark.
- An alder, 13" dia., bears S.61¾°W., 35.9 ft., mkd. T20S R9W S9 BT on bark.
- An alder, 17" dia., bears N.2¼°W., 61.4 ft., mkd. T20S R9W S4 BT on bark.

Corner is located on the E. edge of a creek, 5 ft. wide, course N.30°E.

Each new BT has a 2½"x¼" magnetic nail (Mag Nail) driven at the base on right side center.