

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 399)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor. with brass cap marked:

1/4
S 5 | S 4
1921

from which

An Alder, 12" dia., bears N.12°E., 16 lks., mkd: 1/4 S4 BT.
An Alder, 8" dia., bears S.51°W., 26 lks., mkd: 1/4 S5 BT.

R.M. Morris - 2/11/1971 - C.S. File 55/184

True corner being a brass cap, established by the GLO, to be removed during road construction. From said corner I set a 1 1/2" iron rod, bearing S.65°W., 82.3 ft. From said iron rod, a second iron rod bearing N.25°W., 25.8 ft. Both rods being witness points and both being 1 1/2" in dia., Said restoration being witness by Mr. T. Varley of Cottage Grove, OR.