

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 375-76)

Set an iron post 3 ft.long, 2" dia., 27" in the ground for closing cor. of secs. 4 and 5, with brass cap marked:

T19S R9W

S33

S5 | S4

T20S | R9W

CC
1921

from which

A Maple 14" dia., bears S.38°E., 27 lks. dist. mkd. T20S R9W S4 CC BT.

An Alder 30" dia., bears S.15°W., 61 lks. dist. mkd. T20S R9W S5 CC BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - July 19, 1968 - C.S. File 53/66-67

Found - 1921 GLO brass cap with badly rusted pipe, buried under 48" Cedar log.

14" Maple, now 20" shattered stump, S.38°E., 17.8 ft., no scribe found on unhealed blaze.

30"(?)Alder now 24" stump, S.15°W., 40.3 ft., blaze decayed, no scribe.

Set Brass cap at cor. mkd: County Surveyors Office

T 19 S

CC S 5 | S 4

T 20 S R 9 W

1968

Deposit old corner material alongside.

New BT - 30" Maple N.12°W., 67.6 ft. mkd. CC S4 S5 CS BT.

No other trees available.

Cor. lies 20 ft. E. of small ravine, course NE. and 200 ft. S. of Middle Fork of Smith River.