

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 339500

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 9 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 387-8)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of sec. 9 only, with brass cap marked:

¼ S9
1921

from which

A chittem, 8" dia., bears N.4°E., 103 lks., mkd: ¼ S9 BT.

A vine maple, 6" dia., bears N.1°W., 72 lks., mkd: ¼ S9 BT

Stephen Swinehart, L.S. 2013 - For: USFS, Siuslaw National Forest - July 1983 - M94-77

Found - Brass cap marked ¼ S9 rusted off
1" iron pipe with concrete core (1921)
7" vine maple windfall with no visible marks - root hole, N.1¾°W., 49.1 ft. (Mensch N.1°W., 47.5 ft.)

Set - F.S. Alum. cap & pipe. Buried old pipe alongside.

New BTs- 9" Fir, "¼ S9 BT" bears N.28¾°W., 64.7 ft.

6" Fir, "¼ S9 BT" bears N.9¾°E., 65.0 ft.

We raised a stone mound around the monument.

Fd. BC - 10/2019 - T. Hostetter - C.S. 65/103-13