

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 260 dated April 17, 1877 - (DCSO records Vol. 1 Page(s) 310)

Set ¼ sec. post; from which
An Alder, 5" in dia., N.73½°E., 11 lks.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12507)

The ¼ sec. cor. of secs. 28 & 33, at record bearing & dist. from the orig. BT, as follows:
An Alder, 26" dia., bears N.73½°E., 11 lks., plainly blazed & healed, but hollow; more recently marked ¼ in bark with an axe.

At the corner point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:
¼ S 28
 S 33
 1953

from which new BTs
A Maple, 20" dia., bears N.66°W., 25 lks., mkd: ¼ S28 BT.
A Fir, 40" dia., bears S.13¼°E., 55 lks., mkd: ¼ S33 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 37 Page(s) 15388-9) - Fd. BC & 2 1953 BTs - Set a 6' steel fence post alongside the iron post.

BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1209, surveyed May/Aug. 1984 - (DCSO records Vol. 47 Page(s) 18001) - Fd. BC & 1 orig. BT & 2 1953 BTs.

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23105)

The ¼ sec. cor. of secs. 28 and 33, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.
from which the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54
A decayed fir stump, 52" dia , bears S.13¼°E., 36.3 ft., no marks visible.
A decayed maple stump, 22" dia., bears N.66°W., 16.5 ft., no marks visible. continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

and new bearing trees

A fir, 9" dia, bears S.13°W., 2.3 ft., mkd. ¼ S33 BT.

A fir, 8" dia , bears N.5½°W., 16.3 ft. mkd. ¼ S28 BT.

A steel fence post is alongside the cor.