

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 16 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 342-3)

Set a sandstone, 12x10x7", 8" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which
 A fir, 42" dia., bears S.16°W., 13 lks., mkd: ¼ S BT.
 A fir, 16" dia., bears N.5°W., 12 lks., mkd: ¼ S BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 387)

Intersect the old ¼ sec. cor., which is sandstone, 5x8x7" above ground, firmly set, marked & witnessed as described by the surveyor general. Hereafter, this cor. will refer to sec. 16 only. I obliterate marks on N face of stone, & mark ¼ on S face; also obliterate marks on former BT N of line, & take new BT.
From the corner
 (New BT) A vine maple, 6" dia., bears S.25°E., 30 lks., mkd: ¼ S16 BT.
 (Old BT) A fir, 45" dia., bears S.16°W., 13 lks., mkd: ¼ S16 BT.

Stephen Swinehart, L.S. 2013 - For: USFS, Siuslaw National Forest - July 1983 - M94-77

Found - Broken stone monument with no visible marks (1891)
 27" fir stump with healed face & county location tag
 bears N.10°W., 7.9 ft. (N.5°W., 7.9 ft. Thiel)
Set - F.S. alum cap & pipe. Buried stone.
BTs - 8" Alder "¼ S16 BT" bears S.83°E., 54.1 ft.
 19" hemlock, "¼ S16 BT" bears S.6½°E., 75.0 ft.
We raised a stone mound around our monument.

Fd. BC - 10/2019 - T. Hostetter - C.S. 65/103-13