

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 4 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 376-77)

Set an iron post 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor. of sec. 4 only, with brass cap mkd:

1/4 S4
1921

from which

An Alder 10" dia., bears S.59°E., 18 lks. dist. mkd. 1/4 S4 BT.

A Fir 20" dia., bears S.6°W., 21 lks. dist. mkd. 1/4 S4 BT.

Survey by Tom O. McCullough - For: U.S. Forest Service - April 1970 - C.S. File 55/148-5

Found corner established in 1921 by Collier, which is a cement filled pipe set in 1921 by GLO, from which

40" Fir bears S.2°W., 12.4 ft., evidence of face.

Set 2" x 30" Iron pipe with brass cap mkd: T 20 S R 9 W

4

Set pipe alongside corner.

1970

Set fence post with signs ± 5 ft. S.

650

facing E.