

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Wm. Thiel under Contract #260 dated April 17, 1877 - (DCSO records Vol. 1 Page(s) 305) and (Pg. 320)

Set post on flat spur, for corner to secs. 33, 34, 4 and 3; from which

- A Hemlock 8" dia., bears S.21°E., 36 lks. dist.
- A Hemlock 15" dia., bears N.46°E., 67 lks. dist.
- A Fir 30" dia., bears N.14°W., 46 lks. dist.
- An Alder 16" dia., bears S.63½°W., 67 lks. dist.

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 3 Page(s) 953)

The sec. cor. which is a post 30" above ground 3" sq., marked T20S S34 on the NE.; R9W S3 on the SE.; T21S S4 on the SW.; and S33 on the NW. faces with 3 notches on the E. and W. edges. (I obliterated marks on the SE. and SW. faces and added R9W on the NW. face.), from which

- A Hemlock 30" dia., bears N.37°E., 68 lks. dist. mkd. T20S R9W S34 BT.
- A Hemlock 12" dia., bears S.22°E., 37 lks. dist. mkd. T21S R9W S3 BT.
- An Alder 18" dia., bears S.63°W., 67 lks. dist. mkd. T21S R9W S4 BT.
- A Fir 36" dia., bears N.15°W., 46 lks. dist. mkd. T21S R9W S33 BT.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12450-51)

The cor. of secs. 33 & 34 only, determined at record distance from each of the original bearing trees, as follows:

- A Hemlock snag, 40" dia., bears N.38°E., 67 lks. dist., with scribe marks T20 and BT visible on partly decayed face of blaze. (Thiel record, bears N.46°E.; Gesner record, bears N.37°E., 68 lks.)
- A Hemlock 40" dia., bears S.21°E., 36 lks. dist., with scribe marks T21 R9 and S3 visible on opened and decaying blaze.
- An Alder stump, 20" dia., bears S.63½°W., 67 lks. dist. with only axe marks remaining.
- A Fir 58" dia., bears N.14°W., 46 lks. dist., plainly blazed and healed.

At the corner point
(Cont. Next Page)

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post, 3 ft. long, 2" dia., 28" in the ground,
with brass cap mkd: T 20 S R 9 W
 S 33 | S 34
 T 21 S R 9 W
 S 4
 1953

from which a new bearing tree:
A Cedar 54" dia., bears N.88½°E., 48 lks. dist., mkd. T20S
R9W S34 BT. (This Cedar is the line tree mentioned by
Thiel as being 46 lks. dist., and by Gesner as being 48
lks. dist., and has healed blazes on E. and W. sides
slightly S. of center. No other suitable bearing tree
is available in the NE. quadrant.)

Cor. Fd. OK and used in BLM resurvey by Peter A. Peterson,
Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr.
1966/May 1967 (DCSO records Vol. 34 Page(s) 14219)

Fd. pipe bent - straightened Feb. 14, 1984 by L. Roberts -
M 90-53. Buried mag. marker under pipe and cap.

BLM resurvey by Joel E. Robb, Cadastral Surveyor, under Group
#1209, surveyed May/Aug. 1984 - (DCSO recs Vol. 47 Pg 17998)

The Sec. cor., monumented with an iron post, 2" dia., firmly
set, projecting 8" above ground, with brass cap mkd. in 1953,
from which the remains of the original bearing trees:
A sawed Hemlock stump 25" dia., bears S.21°E., 36 lks.
dist., no marks visible.
A sawed Fir stump 72" dia., bears N.14°W., 49 lks. dist.,
with healed blaze.
and the remains of a bearing tree mkd. by Tillman & Gawron:
A sawed Cedar stump 54" dia., bears N.88½°E., 48 lks.
with fragmentary scribe marks visible on open blaze.
and new bearing trees:
A Fir 3" dia., bears N.67¼°W., 22½ lks. dist. mkd. X BT.
A Fir 6" dia., bears N.74¼°W., 90½ lks. dist. mkd. T20S
R9W S33 BT.

BLM corrective remonumentation and rehabilitation of certain
corners by Edith M Forkner, Cadastral Surveyor, under Group
#2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol.
58 Page(s) 23079)

The cor. of secs. 33 & 34 only, monumented with an iron post,
2" dia., firmly set, projecting 8" above ground, with brass
cap (properly) mkd.
continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees
A shell of a decayed hemlock stump, Size indeterminate,
bears S.21°E. , 23.8 ft. , with a healed blaze.
A fir Stump, 70" dia. , bears N.14°W., 32.3 ft., no marks
visible.
and the remains of the Original line tree mkd. by Thiel in
1891, recovered and remarked as a bearing tree by Tillman and
Gawron in 1953-54
A shell of a cedar stump, size indeterminate, bears
N.88½°E., 31.7 ft., no marks visible.
and the bearing trees mkd. by Robb in 1984
A fir, 14" dia., bears N.67¼°E., 14.9 ft., no marks
visible Add the marks T20S R9W S34 BT and a Mag Nail on
the right side center.
A fir, 17" dia., bears N.74¼°W., 59.7 ft., with a healed
blaze.
A steel fence post with a Property sign is alongside the cor.