

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 260 dated April 17, 1877 - (DCSO records Vol. 1 Page(s) 306

Set post to secs. 27, 28, 33, & 34 on SE slope; from which

A fir, 24" dia., bears N.62½°E., 48 lks.

A fir, 36" dia., bears S.34½°E., 3.42 chs.

A fir, 10" dia., bears S.40½°W., 48 lks.

A fir, 30" dia., bears N.17¾°W., 49 lks.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12495

The cor. of secs. 27, 28, 33, & 34 determined at record bearing & dist. from the orig. NW BT, as follows:

A fir, 32" dia., bears N.17°45'W., 49 lks., with scribe marks BT visible on blaze which has been partly burned, healed, and cut open.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S	R9W
S 28	S 27
S 33	S 34
1953	

from which new BTs

A fir, 8" dia. bears N.13½°E. 30 lks. mkd: T20S R9W S27 BT

A fir, 14" dia. bears S.10°E. 3½ lks. mkd: T20S R9W S34 BT

A fir, 8" dia. bears S.56¼°W. 39 lks. mkd: T20S R9W S33 BT

A fir, 10" dia., bears N.51°45'W., 27 lks., mkd: T20S R9W S28 BT.

Fd. & used on BLM dependent resurvey by Harvey E. Wofford, Cadastral Surveyor under Group #1090, surveyed April/May 1982 - (DCSO records Vol. 45 Page(s) 17456-7)

BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1209, surveyed May/Aug. 1984 - (DCSO records Vol. 47 Page(s) 18000)

The cor. of secs. 27, 28, 33, & 34, monumented with an iron post, 2" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd., from which an orig. BT

A fir, 37" dia., bears N.17¾°W., 49 lks., no marks visible on opened blaze.

and the remains of BTs mkd. by Tillman & Gawron

A fir, 14" dia., bears N.15½°E., 30 lks., with healed blaze. (Rec. N.13½°E.)

continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 21" dia., bears S.10°E., 3½ lks., with healed blaze
A fir snag, 12" dia. bears S.56¼°W. 39 lks., with scribe
marks S R9W S33 B visible on open blaze.
A fir, 13" dia., N.51¾°W., 27 lks., with healed blaze.
and a new BT
A fir, 20" dia., bears S.47¼°W., 37 lks., mkd: T20S R9W
S33 BT.

Les Roberts - Ted Baker, Note Keeper - Oct. 1988 - C.S.
63/85-1

Found- 1953 GLO Brass cap set firmly in the ground.
16" fir, N.14°E., 20.0 ft. (scar vis) 1953 BT (Rec.
N.13½°E., 19.8')
18" fir, S.51°W., 24.3 ft. (scar vis) 1953 BT (Rec.
S.56¼°W., 25.7 ft.)
24" fir, N.52°W., 18.0 ft. (scar vis.) 1953 BT (Rec.
N.51 3/4°W., 17.8 ft.)
28" fir, S.08°E., (scar vis.) 1953 BT. (Rec. S.10°E.,
2.3 ft.)
Because of planned logging activity in this area in the near
future I SET the following R.P.'s:
16" fir, N.26°E., 17.95 ft. to 6" steel spike.
18" fir, S.48°W. , 24.30 ft. to 6" steel spike.
28" fir, S.32°E. , 1.75 ft. to 6" steel spike.