TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 339)

Set a post, 48" long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which
A fir, 16" dia., bears S.62°W., 10 lks., mkd: ¼ S BT.
A fir, 12" dia., bears S.39½°E., 23 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12500

The ¼ sec. cor. of secs. 21 & 22, determined at record bearing & dist. from each of the orig. BTs, as follows:
A fir, 22" dia., bears S.39½°E., 23 lks., mkd: ¼ S BT on bark blaze.
A fir, 28" dia., bears S.62°W., 10 lks., mkd: ¼ S BT on bark blaze.
At the corner point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked: ¼
S 21|S 22
1953
from which a new BT
A fir, 54" dia., bears S.85°W., 18 lks., mkd: ¼ S21 BT.

Fd & used on BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1209, surveyed May/Aug. 1984 - (DCSO records Vol. 47 Page(s) 18007) - FD. BC & 3 BTs.

Fd. Ok by Les Roberts, 12/1982 - M90-31