

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 340)

-----  
Set a post, 5 ft. long, 5" sq. 24" in the ground, for cor. to secs. 15, 16, 21, & 22, marked T20S S15 on NE, R9W S22 on SE, S21 on SW, S16 on NW faces, with 3 notch on S & E edges; from which

- A fir, 21" dia., bears N.44½°E., 55 lks., mkd: T20S R9W S15 BT.
- A barberry, 4" dia., bears S.89°E., 12 lks., mkd: T20S R9W S22 BT.
- A barberry, 6" dia., bears S.64°W., 29 lks., mkd: T20S R9W S21 BT.
- A fir, 18" dia., bears N.72½°W., 66 lks., mkd: T20S R9W S16 BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12500-1)

-----  
The cor. of secs. 15, 16, 21, & 22, determined from the orig. BTs, as follows

- A fir snag, 40" dia., bears N.39½°E., 55 lks., mkd: T20S R9W S15 BT on bark blaze. (Rec. bearing N.44½°E.)
- A cascara snag, 5" dia., bears S.89°E., 12 lks., with no marks remaining.
- A cascara snag, 8" dia., bears S.64°W., 29 lks., with no marks remaining.
- A fir, 45" dia., bears N.72½°W., 66 lks., mkd: T20S R9W S16 BT on bark blaze.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

|             |             |
|-------------|-------------|
| T20S        | R9W         |
| <u>S 16</u> | <u>S 15</u> |
| S 21        | S 22        |
| 1953        |             |

from which new BTs

- A fir, 48" dia., bears N.52½°E., 93 lks., mkd: T20S R9W S15 BT.
- A fir, 48" dia., bears S.32°E., 106 lks., mkd: T20S R9W S22 BT.
- A fir, 36" dia., bears S.87°W., 225 lks., mkd: T20S R9W S21 BT.

FD. BC & 3 BTs (SE BT destroyed by Rd. construction) by Les Roberts, Dec. 1982 - M90-31

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23101-2)

-----  
The cor. of secs. 15, 16, 21, & 22, monumented with an iron post, 2" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree  
A decayed fir stump, size indeterminate, bears N.39½°E., 36.3 ft., no marks visible.

and the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54

A decayed fir stump, 36" dia, bears N.52½°E., 61.4 ft., no marks visible.

A fir stump, 33" dia, bears S.87°W., 150.4 ft., no marks visible. (Record, 148.5 ft.)

and new bearing trees

A fir, 20" dia., bears N.11°E., 20.7 ft. mkd. T20S R9W S15 BT.

A fir, 13" dia, bears S.4½°W. , 54.1 ft. mkd. T20S R9W S21 BT.

A fir, 22" dia, bears N.81°W., 75.8 ft. mkd. T20S R9W S16 BT.

No suitable trees to the SE. available.

Robert Cook - for: Roseburg Forest Product - 6/2020 - M177-17

-----  
Found - 2½" 1953 GLO brass cap up 3" on NE bank of gravel Road. This monument has a 1/2" rebar riser and can be seen easily from the truck.

BT's per BLM Forkner survey 2006-2009 -

27" D.Fir N.11°E., 20.7 ft. with healed face, tag and paint.

22" D.Fir S.04°30'W., 54.1 ft. with healed face tag and paint.

30" D.Fir N.81°W., 75.8 ft. with healed face tag and paint.