

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 341-2)

-----  
A fir, 36" in dia., which I mark for cor. to secs. 9, 10, 15, & 16, marked T20S S10 on NE, R9W S15 on SE, S16 on SW, S9 on NW sides, with 4 notches on S & 2 notches on E sides, for cor. to secs. 9, 10, 15, & 16; from which

- A fir, 36" dia. bears N.71°E. 46 lks. mkd: T20S R9W S10 BT
- A fir, 15" dia. bears S.40°E. 39 lks. mkd: T20S R9W S15 BT
- A fir, 40" dia. bears S.9°W., 29 lks. mkd: T20S R9W S16 BT
- A fir, 36" dia. bears N.19°W., 36 lks. mkd: T20S R9W S9 BT

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 386-7)

-----  
The cor. of secs. 9, 10, 15, & 16, which is a fir, 40" dia., marked & witnessed as described by the surveyor general, except that the SW BT is dead. I take a new BT  
From the corner

- (Old BT) A fir, 40" dia., bears N.71°E., 46 lks., mkd: T20S R9W S10 BT.
- (Old BT) A fir, 18" dia., bears S.40°E., 39 lks., mkd: T20S R9W S15 BT.
- (New BT) An alder, 8" dia., bears S.61°W., 24 lks., mkd: T20S R9W S16 BT.
- (Old BT) A fir, 40" dia., bears N.19°W., 36 lks., mkd: T20S R9W S9 BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12503)

-----  
The cor. of secs. 9, 10, 15, & 16, marked by a fir, 47" dia., marked T20S R9W S10 on NE, R9W S15 on SE, S16 on SW, S9 on NW sides, from which

- A fir, 50" dia., bears N.71°E., 46 lks., mkd: T20S R9W S10 BT on bark blaze. (Thiel BT)
- A fir, 24" dia., bears S.40°E., 39 lks., mkd: T20S R9W S16 BT on bark blaze. (Thiel BT)
- A fir snag, 40" dia., bears S.9°W., 29 lks., with partial scribe marks visible on bark blaze. (Thiel BT)
- An alder stump, 24" dia. bears S.61°W. 24 lks. with faint scribe marks still vis. on decaying blaze. (Mensch BT)
- An alder, 10" dia. bears S.68½°W. 20 lks., marked T20S R9W S16 BT. (New BT)
- A fir, 50" dia., bears N.19°W., 36 lks., mkd: T20S R9W S9 BT on bark blaze. (Thiel BT) Continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Stephen Swinehart, L.S. 2013 - For: U.S. Forest Service - July 1983 - M94-77

- 
- Found - Orig. fir corner tree, now 44" with dead top (36").  
58" fir stump with blaze, N.70°E., 31.5 ft. (36" N.71°E., 30.4 ft.)  
58" fir stump, N.13°W., 26.6 ft. (36", N.19°W., 22.8 ft.)  
38" fir stump, S.4°W., 22.1 ft. (38", S.9°W., 19.1 ft.)  
29" fir stump, S.43°E., 29.3 ft. (15", S.40°E., 30.4 ft.)
- Set - 2" brass caps & 1"x30" iron pipes for reference monument. One marked "S9 RM" is N.20°27'W., 41.33 ft. from the corner. The other one marked "S10 RM" is N.70°06'E., 37.88 ft. from the corner.  
We raised stone mounds around the monuments.

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23103-4)

-----

The cor. of secs. 9, 10, 15, & 16, monumented with the original corner tree, a fir snag, 45" dia., with illegible scribe marks visible on bark blazes on the NE. , SE. , SW. , and NW. faces, from which the remains of the original bearing trees

- A decayed fir stump, 57" dia , bears N.71°E., 31.9 ft., no marks visible. (Record, 30.4 ft.)
- A decayed fir stump, 22" dia, bears S.46°E., 29.0 ft., no marks visible. (Record, S.40°E., 25.7 ft.)
- A decayed fir stump, 36" dia, bears S.3/4°W., 22.9 ft., no marks visible. (Record, S.9°W., 19.1 ft.)
- A decayed fir stump, 54" dia , bears N.12°W., 26.7 ft., with illegible scribe marks visible on bark. (Record, N.19°W., 23.8 ft.)

and reference monuments established by Swinehart, in 1983

- An iron post, 1" dia., projecting 4" above ground, bears N.69°51'59"E., 38.12 ft. with brass cap mkd. T20S R9W S10 RM 37.88 LS 2013 1983 and an arrow pointing to the corner. A red carsonite post is alongside the post.
- An iron post, 1" dia., projecting 4" above ground, bears N.20°18'50"W. , 41.36 ft. with brass cap mkd. T20S R9W S9 RM 41.33 LS 2013 1983 and an arrow pointing to the corner. A red carsonite post is alongside the post.

continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the Corner Point

Cut down corner snag and drive an iron rod, 5/8" dia., 30" long, 27" in the center of the stump, with aluminum cap mkd.

T 20 S R 9 W

S 9 | S10

S16 | S15

2006

from which new bearing trees

A fir, 15" dia, bears S.66°E., 38.9 ft. mkd. T20S R9W S15  
BT.

A fir, 20" dia., bears S.48¼°W., 20.3 ft. mkd. T20S R9W  
S16 BT.