

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 400537

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 394)

-----  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of sec. 9 only, with brass cap marked:

¼|  
S 9|  
1921

from which

- A fir, 36" dia., bears S.70°W., 57 lks., mkd: ¼ S9 BT.
- A fir, 24" dia., bears N.83°W., 62 lks., mkd: ¼ S9 BT.

Stephen Swinehart, L.S. 2013 - For: U.S. Forest Service - July 1983 - M94-77

-----  
Found - GLO brass cap marked "¼ S9 1921" with concrete core - cap rusted off.  
22" fir windfall with healed face - face is N.73°E., 40.8 ft. (24" N.83°W., 40.9 ft.)  
30" fir windfall with possible face - face is S.87°W., 23.0 ft. (36" S.70°W., 37.6 ft.)  
Set - FS alum. cap & pipe. Buried the old pipe alongside.  
New BTs- 16" Hemlock, "¼ S9 BT" bears S.72½°W., 93.1 ft.  
12" Alder, "¼ S9 BT" bears N.51¾°W., 46.3 ft.  
We raised a stone mound around the monument.