

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs 3, 4, 9, & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 393)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for cor. of secs. 3, 4, 9, & 10, with brass cap marked:

T20S R9W
S 4 | S 3
S 9 | S 10
1921

from which

- A cedar, 18" dia., bears N.33°E., 38 lks., mkd: T20S R9W S3 BT.
- A cedar, 18" dia., bears S.57°E., 60 lks., mkd: T20S R9W S10 BT.
- A chittem, 10" dia., bears S.74°W., 74 lks., mkd: T20S R9W S9 BT.
- A chittem, 12" dia., bears N.38°W., 62 lks., mkd: T20S R9W S4 BT.

Douglas Co. Surveyors Office - Milo Godfrey, Deputy - Wm. Stoffel - Mike Stone - Sept. 1964 - C.S. File 53/66-46

Corner set on an affidavit of Fred Zeigler, see reverse side of orig. field notes in C.S. File 53/66. Brass cap & BT mentioned in affidavit have been washed away.

Set - Brass cap at cor. mkd: County Surveyors Office 1964 T20S R9W
S 4 | S 3
pile boulders around corner. S 9 | S 10

New BTs- 50" D.Fir N.70°W., 62.4 ft., mkd: T20S R9W S4 CS BT
60" D.Fir N.30°E., 151.1 ft., mkd: T20S R9W S3 CS BT
Clear cut area SE & SW BT of corner. No trees available.

Note - Corner is in bottom of draw, approx. 75 ft. from forks in draw up left fork

FD. Ok by Douglas Co. Surveyors Office - Ed Monrean - 1/19/1976 - C.S. File 59/2-8

Don Peel - 6/1982 - M93-28 - Fd. BC & 2 BTs.