

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 346)

Set a post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on N face; from which

 A fir, 30" dia., bears N.54°W., 50 lks., mkd: ¼ S BT.

 A cedar, 15" dia., bears S.49½°E., 42 lks., mkd: ¼ S BT.

A Cliff, 6 ft. high is S. 10 lks.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12501-2)

The ¼ sec. cor. of secs. 15 & 22, at record bearing & dist. from each of the orig. BTs, as follows:

 A fir, 50" dia., bears N.54°W., 50 lks., mkd: ¼ S on bark blaze.

 A rotted cedar stump, 24" dia., bears S.49½°E., 42 lks., with no marks remaining.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:

¼	<u>S 15</u>
	<u>S 22</u>
	1953

from which a new BT

 A cedar, 22" dia., bears S.48°E., 47 lks., mkd: ¼ S22 BT.

FD. Ok by Les Roberts, 2/25/1983 - M93-63

BLM dependent resurvey by Joel E. Robb, Cad Surveyor, Group #1209 surveyed May/Aug. 1984 - (DCSO recs Vol. 47 Pg 18006)

The ¼ sec. cor. of secs. 15 & 22, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd., from which the remains of an orig. BT

 A fir snag, 55" dia., bears N.54°W., 50 lks., with scribe marks ¼ S visible on bark.

and new BTs

 A sawed fir stump, 36" dia., bears S.72½°W., 73 lks., mkd: ¼ S22 BT.

 A cedar, 35" dia., bears N.30°W., 80 lks., mkd: ¼ S15 BT.

From this point, Lane County Public Works Dept. triangulation station "ROMAN 2 ECC 1973" bears N.9°30'E., 475.29 chs. monumented with an iron post, 2½" dia. firmly set, projecting 6" above ground, with brass cap mkd: ROMAN 2 ECC 1973.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Ron Rice, NW Land Surveying - April 2013 - C.S. File 65/78-29 ----- Found - 1953 GLO brass cap with the following accessories: 55" D.Fir snag bears N.54°W., 33.0 ft. - no marks 36" D.Fir stump bears S.72½°W., 48.2 ft. - no marks 42" R.Cedar bears N.30°W., 52.8 ft. - healed face New - 43" R.Cedar bears N.89°W 11.4 ft. - blazed, scribed ¼ S 15 BT. 13" Alder bears S.40°E., 28.4 ft. - bark scribed ¼ S22 BT Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags. Decl. 16°E.</p>
<p>Robert Cook - for: Roseburg Forest Product - 6/2020 - M177-17 ----- Found - 1953 GLO brass cap up 1" with steel post riser. Monument lies about 25 ft. West of a drainage. 1953 GLO BTs found - 55" D.Fir snag N.54°W., 33.0 ft. with tag. 43" Cedar N.30°W. 52.8 ft. with healed face, tag and paint. BTs per CS File 65/78-29 - 44" Cedar N.89°W., 11.4 ft. with scribing visible, tag and paint. 14" Alder S.40°E., 28.4 ft. with barkscribing tag and paint.</p>