

PRIMARY CORNER DESCRIPTION Center 1/4 Sec. 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1209, surveyed May/Aug. 1984 - (DCSO records Vol. 47 Page(s) 18002-3)

Point for the center ¼ sec. cor. of sec. 10, at intersection with the E & W center line.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
T20S R9W
C ¼ S 10
1984

from which
A fir, 8" dia., bears N.17¼°E., 121 lks., mkd: C¼ S10 BT.
A maple, 6" dia., bears N.60½°W., 22½ lks., mkd: C¼ S10 BT

Fd. BC & BTs 10/2016 by R. Rice M172-65

BLM Dependent Resurvey by Jason A Lightbown, Cadastral Surveyor, Under Group No. 2841, Surveyed June/Oct. 2016 - (DCSO records Vol. 59 Page(s) 23610)

The center ¼ sec. cor. of sec. 10, monumented with an iron post, 2½" dia., firmly set, projecting 1" above ground, with a brass cap (properly) mkd.
from which the bearing trees mkd. by Robb in 1984
A fir, 18" dia., bears N.17¼°E., 79.9 ft., with a healed blaze.
A maple, 16" dia., bears N.64°W., 15.5 ft., with a healed blaze (Record, N.60½°W., 14.9 ft.).

Jerry Estabrook - For: Roseburg Resources - 4/2020 - M177-2

Found - A 2½" iron pipe with brass cap (properly) marked.
An 18" Fir with healed face and tag bears N.17°15'E., 79.9'.
A 16" Fir with healed face and tag bears N.64°W., 15.5'.
New BTs- A 7" Maple, bark scribed "C¼ S10 BT" with X-Chop and tag bears N.34°E., 3.0' to a spike at side center.
A 14" Maple, face scribed "C¼ S10 BT" with X-Chop and tag bears N.82°W., 25.8' to a spike at side center.
BO Tied- A steel post bears East 1.0'.
Lat. And Long. per Garmin Etrex hand held GPS:
N: 43°50'56.3" W: 123°45'28.6"