

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 395)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap marked:

$\frac{1}{4}$ $\frac{S}{S}$ $\frac{3}{10}$

from which

A yew, 18" dia., bears N.58°W., 51 lks., mkd: $\frac{1}{4}$ S3 BT.

A fir, 18" dia., bears S.32°W., 18 lks., mkd: $\frac{1}{4}$ S10 BT.

Donald Peel - For: International Paper - 6/8/1982 - M92-28

Found - 1921 US GLO brass cap

New BTs- 42" fir, S.43°W., 25.0 ft.

34" fir stump, N.13°E., 47.7 ft. (dist. to R/R spike in top)

BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1209, surveyed May/Aug. 1984 - (DCSO records Vol. 47 Page(s) 18003)

The $\frac{1}{4}$ sec. cor. of secs. 3 & 10, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with brass cap mkd:

$\frac{1}{4}$ $\frac{S}{S}$ $\frac{3}{1921}$

from which a BT mkd. by person(s) unknown

A fir, 41" dia., bears S.41 $\frac{1}{2}$ °W., 38 lks., with scribe mark

S visible on opened blaze.

and a new BT

A fir, 41" dia., bears S.36°W., 51 lks., mkd: $\frac{1}{4}$ S10 BT.

No other suitable trees available.

Ronald L Rice - Oct. 2016 - Oxbow Timber 1 LLC - M172-65

Found - 1921 GLO brass cap with the following accessories:

58" D.Fir bears S.41 $\frac{1}{2}$ °W., 25.1', healed face.

44" D.Fir bears S.36°W., 33.7', healed face.

34" D.Fir stump bears N.13°E., 47.7' to RR spike on top.

13" D.Fir bears N.7 $\frac{1}{4}$ °E., 45.5', scribing visible (2016 BLM)

Alum. post adjacent to corner.

continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Jason A Lightbown, Cadastral Surveyor, Under Group No. 2841, Surveyed June/Oct. 2016 - (DCSO records Vol. 59 Page(s) 23607)

The ¼ sec. cor. of secs. 3 and 10, perpetuated by Peel, in 1982, not reported by Robb in 1984; monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with a brass cap (properly) mkd.

from which the remains of a bearing tree mkd. by Peel

A fir stump with railroad spike set in top, 32" dia., bears N.12°E., 47.5 ft., with illegible scribe marks visible on open blaze.

A fir, 58" dia., bears S.4½°W., 25.1 ft., with a healed blaze. This tree was incorrectly reported as being by person's unknown by Robb.

and a bearing tree mkd. by person(s) unknown

A fir, 13" dia., bears N.7° E., 45.5 ft., with a healed blaze.

and a new bearing tree

A fir, 44" dia., bears S.32¼°W., 25.9 ft., mkd. ¼ S10 BT. Each new bearing tree has a 2½" x ¼" magnetic nail (Mag Nail) driven at the base on right side center and each new monument established or reestablished has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.