

PRIMARY CORNER DESCRIPTION AP on Line bet. Secs. 27 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 260 dated April 17, 1877 - (DCSO records Vol. 1 Page(s) 307)

On top of main ridge; a steep canyon due E with Smiths River below. Smiths River, c N.5°W. Canyon of Scare Creek is visible S.5°E.

Marked a fir, 24" in dia., on top of ridge, for witness post; from which

A fir, 8" dia., bears N.27½°E., 18 lks.

A fir, 12" dia., bears S.66½°E., 30 lks.

This post is more apt to remain as it is out of reach of fire.

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 324-5)

Intersect N & S line 10 lks. N of witness post to secs. 27 & 34, which is a fir, 24" in dia., marked T20S S27 on N side & R9W S34 on S sides; from which

A fir, 8" dia., bears N.27½°E., 18 lks., mkd: T20S R9W S34 WC BT.

A fir, 12" dia., bears S.66½°E., 30 lks., mkd: T20S R9W S34 WC BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12496)

Thiel's witness point, a solid fir snag, plainly blazed on N & W sides, from which

An uprooted fir, 24" dia., plainly blazed & healed, the stump hole of which bears N.27½°E., 18 lks.

A fir stump, 18" dia., S.66½°E., 30 lks., with no marks remaining on bark blaze.

This now becomes an angle point. I mark AP T20S R9W S27 on N & S34 on S sides of fir snag, and mark new BTs as follows:

A fir, 8" dia., bears N.86°W., 17 lks., mkd: AP T20S R9W S27 BT.

A fir, 9" dia., bears S.63°E., 34 lks., mkd: AP T20S R9W S34 BT.

The angle point is located on top of a high ridge, bears N.20°W., & S.20°E., at edge of grassy opening, bears N.60°W., & S.60°E.

continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 462200

PRIMARY CORNER DESCRIPTION AP on Line bet. Secs. 27 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Harvey E. Wofford, Cadastral Surveyor under Group #1090, surveyed April/May 1982 - (DCSO records Vol. 45 Page(s) 17455)

The angle point of secs. 27 & 34 monumented with a root hole, from which the remains of a BT mkd. by Tillman & Gawron:

A fir stump, 15" dia., bears S.63°E., 34 lks. with scribe marks AP T20S R9W S34 BT visible on an open blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 12" in the ground, to solid rock & encircled with a mound of stone, 4 ft. base, to top, with brass cap marked:

AP
T20S R9W
S 27
S 34
1983

from which new BTs

A fir, 14" dia., bears S.19¼°E., 254 lks., mkd: AP T20S R9W S34 BT.

A fir, 15" dia., bears N.29½°W., 93 lks., mkd: AP T20S R9W S27 BT.

The corner point is located on top of a spur, slopes N.20°W., at edge of timber, bears N.20°W., and S.20°E.