

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 321)

-----  
A Fir 18" dia., which I mark for corner to secs. 35, 2, 3 and 34, T20S S35 on NE.; R9W S2 on SE.; T21S S3 on SW.; S34 on NW. sides, from which 2 notches on E. and 4 notches on W. sides; from which

An Alder 15" dia., bears N.47°E., 56 lks. dist. mkd. T20S R9W S35 BT.

A Maple 12" dia., bears S.28°E., 33 lks. dist. mkd. T21S R9W S2 BT.

A Fir 15" dia., bears S.25½°W., 41 lks. dist. mkd. T21S R9W S3 BT.

A Fir 42" dia., bears N.88°W., 78 lks. dist. mkd. T20S R9W S34 BT.

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 1 Page(s) 367) and Vol. 3 Pg. 939)

-----  
The cor. to secs. 34 & 35, which is a Fir tree, 18" dia., mkd. T20S S35 on the NE.; R9W on the SE. sides, from which

An Alder 15" dia., bears N.47°E., 56 lks. dist. mkd. T20S R9W S35 BT.

A Maple 12" dia., bears S.28°E., 33 lks. dist. mkd. T21S R9W S2 BT.

A Fir 18" dia., bears S.25°30'W., 40 lks. dist. mkd. T21S R9W S3 BT.

A Fir 42" dia., bears N.22°W., 75 lks. dist. mkd. T20S R9W S34 BT.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12452)

-----  
The cor. of secs. 34 and 35 only, marked by a Fir 38" dia., bearing healed blazes on N., S., E., and W. sides, and scribed in the bark T20 S35 on NE. and R9W S3 on SE. sides, from which the remaining original bearing trees:

A double Maple 16" dia., bears S.18°E., 36 lks. dist., with blaze rotted. (Rec., bears S.28°E., 33 lks.)

A Fir 30" dia., bears S.25½°W., 42 lks. dist., plainly blazed and healed. (Thiel record, 41 lks. dist.; Gesner record, 40 lks. dist.)

A Fir 70" dia., bears S.88°W., 75 lks. dist. mkd. T20S R9W S34 BT on bark blaze. (Thiel record, bears N.88°W., 78 lks. dist.; Gesner record, bears N.22°W., 75 ks. dist.)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, (South)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

and new bearing trees:

A Cedar 24" dia., bears N.44°E., 65 lks. dist. mkd. T20S R9W S35 BT.

A Hemlock 24" dia., bears N.11°W., 39 lks. dist. mkd. T20S R9W S34 BT.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14220)

-----  
The cor. of secs. 34 & 35 only, determined in the center of a stump hole, from which the remaining original bearing trees:

The stump hole, of a fallen Maple 28" dia., bears S.18°E., 36 lks. dist., with healed blaze.

A stump hole bears S.25½°W., 42 lks. dist. (Rec. 40 lks.)

A Fir 75" dia., bears S.88°W., 75 lks. dist. with healed blaze.

and bearing trees mkd. by Tillman in 1953:

A Cedar 30" dia., bears N.44°E., 65 lks. dist., with healed blaze.

A stump hole, bears N.11°W., 39 lks. dist.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 20 S R 9 W

S 34 | S 35

S 3

T 21 S R 9 W

1967

from which a new bearing tree:

A Fir 50" dia., bears N.46°W., 155 lks. dist. mkd. T20S R9W S34 BT.

Ronald L Rice - For: Oxbow Timber 1 LLC - Nov. 2015 - M170-29

Found - BLM brass cap dated 1967

44" R.Cedar bears N.44°E., 43.8' (record 42.9')  
- healed face

75" D.Fir bears S.88°W., 47.4' (record 49.5')  
-healed face

Record 50" fir bearing N.46°W., 155 lks. - now a stump with rotted face not tied this survey

New BT - 20" D.Fir bears N.48°W., 47.9' - blazed, scribed  
T20S R9W S34 BT

Steel post adjacent to corner