TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 324)

Set a post, 3 ft. long, 3" sq., 12" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which
A fir, 24" dia., bears N.24½°W., 88 lks., mkd: ¼ S BT.
A fir, 18" dia., bears S.34°E., 28 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12481

Point for the ¼ sec. cor. of secs. 34 & 35, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked:

¼
S 34 | S 35
1953

from which
A fir, 7" dia., bears S.16½°E., 24½ lks., mkd: ¼ S35 BT.
A fir, 8" dia., bears N.41°W., 3 lks., mkd: ¼ S34 BT.

Fd. Ok by Les Roberts, 2/19/1984 - M96-26 & C.S. File 58/280