

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 343-4)

Set a post, 5 ft. long, 5" sq. 24" in the ground, for cor. to secs. 22, 23, 26, & 27, marked T20S S23 on NE, R9W S26 on SE, S27 on SW, S22 on NW faces, with 2 notches on S & E edges; from which

- A maple, 12" dia., bears N.83½°E., 29 lks., mkd: T20S R9W S23 BT.
- A maple, 15" dia., bears S.49½°E., 40 lks., mkd: T20S R9W S26 BT.
- An alder, 8" dia., bears S.64°W., 46 lks., mkd: T20S R9W S27 BT.
- A fir, 24" dia., bears N.50°W., 180 lks., mkd: T20S R9W S22 BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12483-4)

The cor. of secs. 22, 23, 26, & 27, determined from the orig. BTs, as follows:

- A maple, 20" dia., bears N.83½°E., 29 lks., plainly blazed & healed.
- A maple, 26" dia., bears S.49½°E., 40 lks., plainly blazed & healed.
- An alder, 16" dia., bears S.64°W., 46 lks., with previously opened blaze now decayed.
- A fir, 42" dia., bears N.50°W., 80 lks., with no marks remaining. (Rec. 180 lks.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap marked:

T20S	R9W
<u>S 22</u>	<u>S 23</u>
S 27	S 26
1953	

from which new BTs

- An Alder, 20" dia., bears N.9°E., 37 lks., mkd: T20S R9W S23 BT.
- A Cedar, 20" dia., bears S.47°E., 50 lks., mkd: T20S R9W S26 BT.
- A Cedar, 18" dia., bears S.4°W., 71 lks., mkd: T20S R9W S27 BT.
- An Alder, 23" dia., bears N.52°W., 59 lks., mkd: T20S R9W S22 BT.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM remonumentation of Orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 37 Page(s) 15386) - Fd. BC & 4 BTs - Set a 6' steel fence post alongside the iron post.

BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1209, surveyed May/Aug. 1984 - (DCSO records Vol. 47 Page(s) 17996)

The cor. of secs. 22, 23, 26, & 27, monumented with an iron post, 2" dia, with a brass cap, firmly set, projecting 6" above ground, alongside of which is a steel fence post, firmly set, projecting 4 ft. above ground, with brass cap (properly) mkd.,

from which the remains of BTs mkd. by Tillman & Gawron

- An Alder snag, 22" dia., bears N.9°E., 37 lks., with scribe marks S23 B visible on a decayed bark blaze.
- A Cedar, 21" dia., bears S.47°E., 50 lks., with scribe marks T20S visible on a partially decayed blaze.
- A Cedar, 20" dia., bears S.4°W., 71 lks., with fragmentary scribe marks visible on a decayed blaze.
- An Alder, 20" dia., bears N.52°W., 59 lks., with scribe marks T20S R9W S22 BT visible on a bark blaze.

and a new bearing tree

- An alder, 23" dia., bears N.67°E., 80 lks., mkd: T20S R9W S23 BT.

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23093-4)

The cor. of secs. 22, 23, 26, & 27, monumented with an iron post, 2" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree

- A decayed fir snag, size indeterminate, bears N.51°W., 53.7 ft., with a healed blaze detached from the tree. (Record, N.50°W. , 52.8 ft.)

and the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54

- A cedar, 28" dia, bears S.47°E., 35.0 ft., with no marks visible on partially healed decayed blaze. (Record, 33.0 ft.)
- A decayed alder stump, 19" dia, bears N.52°W., 37.0 ft., with illegible scribe marks visible on remaining bark. (Record, 38.9 ft.)

continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a bearing tree mkd. by Wofford in 1982
An alder, 24" dia , bears N.67°E., 52.8 ft., with scribe marks T20S R9W S23 BT visible on bark.
and new bearing trees
A fir, 7" dia, bears S.87°W., 34.1 ft., mkd. T20S R9W S27 BT.
A fir, 6" dia., bears N.48½°W., 30.7 ft., mkd. T20S R9W S22 BT.
Corner is located N., 40 ft. from a creek, 1 ft. wide, course S.75°E.