TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 345)

Set a post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which
An Alder, 3" dia., bears S.60°W., 45 lks., mkd: ¼ S BT.
A Hazel, 2" dia., bears S.45°E., 35 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12485-6)

Point for the ¼ sec. cor. of secs. 22 & 23, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 22 | S 23
1953

from which
A double maple, 25" dia., bears S.46½°E., 70 lks., mkd: ¼ S23 BT.
A fir, 10" dia., bears N.21½°W., 118 lks., mkd: ¼ S22 BT.

BLM remonumentation of Orig. corner points by Wm. Glenn & James Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April/May 1967 (DCSO records Vol. 37 Page(s) 15386)

The ¼ sec. cor. of secs. 22 & 23, monumented with an iron post 1" dia., firmly set, projecting 4" above the ground with brass cap (properly) mkd.
from which the remaining BT marked in 1953
A double maple, 25" dia., bears S.45°E., 70 lks., no marks remaining on burned blaze. Rescribed ¼ S23 BT on new blaze. (Rec. S.46½°E.)
and a new BT
A maple, 10" dia., bears N.57½°W., 89 lks., mkd: ¼ S22 BT.
Set a 6 ft. steel fence post alongside the iron post.

BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group #1209, surveyed May/Aug. 1984 - (DCSO records Vol. 47 Page(s) 17997)

The ¼ sec. cor. of secs. 22 & 23, monumented with an iron post 1" dia., firmly set, projecting 2" above the ground with brass cap (properly) mkd.
from which a BT mkd. by Tillman & Gawron
A double maple, 33" dia., bears S.45°E., 74 lks., no marks visible on decayed blaze. (Rec. 70 lks) cont. next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and a new BT
An alder, 10" dia., bears S.28½°W., 100 lks., mkd: ¼ S22 BT.

Ron Rice, NW Land Surveying - April 2013 - C.S. File 65/78-30

Found - 1953 GLO brass cap with the following accessories:
34" Double Maple bears S.45°E., 48.8 ft. - no marks
20" Alder bears S.28½°W., 66.0 ft - bark scribe visible

New - 22" Alder bears S.62°W., 44.6 ft. - bark scribed ¼ S22 BT
25" Maple bears N.58°W., 58.6 ft. - blazed, scribed ¼ S22 BT

Note- Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.
Compass Declination 16° East