

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 345)

-
- A maple, 10" dia, which I mkd T20S S14 on NE, R9W S23 on SE, S22 on SW, S15 on NW faces, with 3 notches on S & 2 notches on E edges for cor. to secs. 14, 15, 22, & 23; from which
- A fir, 42" dia., bears N.87°E., 16 lks., mkd: T20S R9W S14 BT.
 - A maple, 12" dia., bears S.30°E., 10 lks., mkd: T20S R9W S23 BT.
 - A cedar, 15" dia., bears S.51°W., 14 lks., mkd: T20S R9W S22 BT.
 - A cedar, 16" dia., bears N.6°W., 57 lks., mkd: T20S R9W S15 BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12486)

-
- The cor. of secs. 14, 15, 22, & 23, determined at rec. bearing & dist. from each of the remaining orig. BTs, as follows:
- A fir, 50" dia., bears N.87°E., 16 lks., mkd. T20S R9W S14 BT on bark blaze.
 - A cedar, 35" dia., bears S.51°W., 14 lks., with partial scribe marks in negative visible on inside surface of hollow shell.
 - A cedar, 36" dia., bears N.6°W., 57 lks., plainly blazed & healed.

At the corner point
 Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S	R9W
<u>S 15</u>	<u>S 14</u>
S 22	S 23
1953	

- from which new BTs
- A cedar, 23" dia., bears N.55½°E., 27 lks., mkd: T20S R9W S14 BT.
 - A cedar, 24" dia., bears S.38°E., 91 lks., mkd: T20S R9W S23 BT.
 - A fir, 35" dia., bears S.16¼°W., 21 lks., mkd: T20S R9W S22 BT.
 - A cedar, 25" dia., bears N.17°W., 67 lks., mkd: T20S R9W S15 BT.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Ron Rice, NW Land Surveying - April 2013 - C.S. File 65/78-35

Condition Report

Found - 1953 GLO brass cap with the following accessories:

- A fir, 50" dia., bears N.87°E., 16 lks., mkd. T20 R9W S14 BT on bark blaze. (Missing)
- A cedar, 35" dia., bears S.51°W., 14 lks., with partial scribe marks in negative visible on inside surface of hollow shell (35" rotted stump, no marks)
- A cedar, 36" dia., bears N.6°W., 57 lks., plainly blazed & healed. (36" rotted stump, no marks)
- A cedar, 23" dia., bears N.55½°E., 27 lks., mkd: T20S R9W S14 BT. (Missing)
- A cedar, 24" dia., bears S.38°E., 91 lks., mkd: T20S R9W S23 BT. (8' tall stub, face scar)
- A fir, 35" dia., bears S.16¼°W., 21 lks., mkd: T20S R9W S22 BT. (Rolled uproot)
- A cedar, 25" dia., bears N.17°W., 67 lks., mkd: T20S R9W S15 BT. (25" stump, rotted face)
- 8" D.Fir snag bears S.88°W 22.0 ft. - scribing visible (2006 BLM*)
- 20" Maple bears N.19½°W., 27.9 ft. - bark scribed (2006 BLM*)
- 19" Maple in clump bears N.49½°E., 34.4 ft. - bark scribed (2006 BLM*)
- 16" D.Fir bears S.0¼°W., 24.1 ft - healed face (2006 BLM*)

Note - Corner has steel Post adjacent to it. All BTs have red painted bands and yellow tags.

Compass Declination 16 East

* There is no record of a 2006 BLM. - JC DCSO 5/7/2013

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23094-5)

The cor. of secs. 14, 15, 22, and 23, determined at distance, distance intersection from the remains of the original bearing trees

- A shell of a cedar stump, size indeterminate, bears S.65°W., 9.2 ft., no marks visible. (Record, S.51°W.)
- A cedar stump, 37" dia., bears N.13°W., 37.6 ft., no marks visible. (Record, N.6°W.)

and the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54
continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A high cedar stump, 23" dia., bears S.36½°E., 62.2 ft. no marks visible. (Record, S.38°E., 60.1 ft.)

A cedar stump, 25" dia, bears N.21°W., 44.2 ft., with illegible marks visible on partially healed blaze. (Record, N.17°W.)

The 1953-54 iron post was found loosely set, projecting 21" above ground, but over 20 ft. out of position from its relationship to the bearing trees of record and determined to have been moved from its original position.

At the Corner Point

Reset the 1953-54 iron pipe, 2" dia., 36" long, 31" in the ground, with brass cap mkd.

T 20 S R 9 W			
S 15		S 14	
S 22		S 23	
1953			

from which new bearing trees

A maple, 19" dia, bears N.49½°E., 34.4 ft., mkd. T20S R9W S14 BT.

A fir, 15" dia, bears S.¼°E., 24.1 ft., mkd. T20S R9W S23 BT.

A fir, 8" dia, bears S.88°W., 22.0 ft., mkd. T20S R9W S22 BT.

A maple, 18" dia, bears N.19½°W., 27.9 ft., mkd. T20S R9W S15 BT.

Deposit a magnet at the base of the iron pipe.